
















Parts Export

Generated: 2026-04-19 15:54:08

Total Parts: 15

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|---|-------------|--|------------------|---|--|---|---|
|  | COC-00001-D | Black PVC Insulation Tape | CO - Consumables | 3M, Generic / OEM, Tesa, Anchor by Panasonic, Nitto | Black PVC insulation tape designed for electrical insulation, wire repair, cable bundling, and protection of electrical connections. Made from flexible, stretchable vinyl material with strong adhesion and resistance to heat, moisture, abrasion, and weather conditions. Suitable for indoor and outdoor applications. Ideal for electricians, technicians, and DIY users requiring safe and reliable electrical insulation. | Item Type: Insulation Tape Material: PVC Color: Black Length (mm): 55 Width (mm): 55 Height (mm): 20 Weight: 35 g Shipping Weight: 0.04 kg Shipping Dimensions: 6 x 6 x 3 cm | PVC Tape • Electrical Tape • Black Insulation Tape • Flame Retardant • Wire Wrapping |
|  | COC-00003-B | Hot Melt Glue Sticks (11mm, 5pcs Pack) | CO - Consumables | Generic / OEM, 3M, Pro'sKit, Stanley, Bosch | All-purpose hot melt glue sticks suitable for bonding applications in DIY, electronics, crafts, packaging, and general repairs. Designed for use with standard temperature glue guns operating around 200°C and compatible with 11mm diameter glue stick slots. Provides strong adhesion on plastic, wood, fabric, paper, and light materials. | Item Type: Hot Melt Glue Sticks Stick Diameter: 11 mm Pack Quantity: 5 Pieces Shipping Weight: 0.2 kg Shipping Dimensions: 4 x 4 x 4 cm | Glue Sticks • 11mm Glue Stick • Hot Melt Adhesive • Glue Gun Refill • DIY Adhesive |
|  | COC-00004-A | Desoldering Wick 1.5m (100% Copper) | CO - Consumables | Generic | Finely braided 100% copper wick for fast and clean solder removal from electronic joints. Works with a heated soldering iron; flux-assisted for efficient molten solder absorption. Essential for PCB repair, rework, and general electronics maintenance tasks. | Item Type: Desoldering Wick Material: Suitable for Comfortable Desoldering Length: 1.5 m Width: 1.85 mm Thickness: Suitable for Comfortable Desoldering Application: Faster & Cleaner Electronics Desoldering Shipping Weight: 0.008 kg Shipping Dimensions (L x W x H): 6 x 5 x 1 cm | Desoldering Wick • Solder Braid • PCB Repair • 100% Copper • Solder Removal • Flux-Assisted • Electronics Rework • 1.5m |
|  | COC-00007-A | Soldering Flux Paste (10g) | CO - Consumables | Generic / OEM, Noel, Welfix, Mechanic, Pro'sKit | This soldering flux paste is designed to improve solder flow and enhance joint quality during soldering and desoldering operations. It contains high-quality additives and activators for effective bonding. The paste is prepared using standardized formulations to ensure consistent performance. It reduces oxidation and ensures clean and reliable solder joints. Suitable for general-purpose soldering of electrical wires, PCB components, and cables. Ideal for DIY users, students, and professional technicians. | Item Type: Soldering Flux Paste Net Weight: 10 g Color: White / Yellow (as per brand batch) Usage: PCB, Wires, Electrical Components Packaging Type: Small Plastic Container | Flux Paste • 10g • Soldering Flux • PCB Repair • Low Smoke |
|  | COC-00008-A | Desoldering Wick (2.5mm Copper Solder Braid) | CO - Consumables | Noel Solder Wire, Hakko, Velleman, Pro'sKit | Solder wick is composed of fine copper threads braided together. Flux is added to help molten solder flow from unwanted areas (such as PCB pads or jumpers) into the wick. It is commonly used for removing excess solder during PCB repair, rework, and component replacement. Solder wick is also known as desolder braid. This version offers good performance at an affordable price. It efficiently absorbs solder and is suitable for DIY users, repair technicians, and lab use. | Material: Copper (Braided with Flux Coating) Width: 2.5 mm Usage: PCB Desoldering / Rework Shipping Weight: 0.008 kg Shipping Dimensions: 8 x 5 x 2 cm | Desoldering Wick • Solder Braid • 2.5mm • Copper • Flux Coated • PCB Rework • DIY • Repair • Lab Use |
|  | COE-00001-C | CR2025 3V Lithium Coin Cell | CO - Consumables | Panasonic | .Panasonic CR2025 is a 3V lithium coin cell battery designed for long-lasting and reliable power in compact electronic devices. Built using Lithium Manganese Dioxide (LiMnO ₂) chemistry, it offers stable discharge characteristics and a shelf life of up to 10 years under proper storage conditions. Suitable for car key remotes, medical devices, digital watches, calculators, fitness devices, memory backup systems, and other small electronics. | Battery Type: Lithium Coin Cell Battery Size: CR2025 Chemistry: Lithium Manganese Dioxide (LiMnO ₂) Nominal Voltage: 3 V Nominal Capacity: 165 mAh Diameter: 20 mm Height: 2.5 mm Termination Style: Pressure Contacts Operating Temperature: -30°C to +60°C Weight (Unit): 2.3 g Shipping Weight: 0.008 kg Shipping Dimensions: 9.2 x 7.5 x 1 cm | CR2025 Battery • 3V Coin Cell • Lithium Battery • Panasonic Battery • Button Cell |
|  | COE-00002-A | Plusivo 30AWG Silicone Hookup Wire Kit | CO - Consumables | Plusivo | Assorted 30AWG silicone hookup wires, ultra-flexible and durable for electronics and DIY projects. Includes 6 colors × 20m each, totaling 120 meters, perfect for prototyping and wiring. Bonus items like heat shrink tubes, mini wire stripper, and colored wire ties included in a dispensing box. | Brand: Plusivo Item Type: Hookup Wire Kit Wire Gauge: 30 AWG Conductor Material: 0.08 mm Tinned Copper (Stranded) Insulation Material: Silicone Rated Voltage: 300 V Rated Temperature: 200°C Wire Length: 20 meters per color (6 colors) Total Wire Length: 120 meters Weight: 285 g Shipping Weight: 0.27 kg Shipping Dimensions (L x W x H): 15 x 7 x 7 cm | Hookup Wire • Silicone Wire • Stranded Wire • 30AWG • Prototyping • Electronics |

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|---|-----------------------|--------------------------|------------------|--|---|--|---|
|  | EDR-00001-100Z | 0.25W Resistor - 100 Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | 1. 100 ohm Carbon Film Resistors are typical axial-lead resistors, which have much better temperature stability and provide lower noise, and are generally better for high frequency or radiofrequency applications. 2. We made it available in the form of a bunch of different values as required for the project to provide convenience, so you need not find a differently required value resistor at different places while working on your project. | Series: - Resistance (Ohm): 100 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | resistor • 100ohm • carbon film • passive component |
|  | EDR-00001-10K0 | 0.25W Resistor - 10K Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | 1.10K/100? Carbon Film Resistors are typical axial-lead resistors that offer good temperature stability and low noise performance. They are suitable for general-purpose electronic circuits, including high-frequency and RF applications. 2. These resistors are available in multiple values for project flexibility, eliminating the need to source different resistor values separately. | Power: 1/4 W Resistance: 100 ? Resistance Tolerance: 5% Type: Carbon Film Resistors | Through Hole • carbon film • 10k resistor • 0.25w • passive • axial |
|  | EDR-00001-1K00 | 0.25W Resistor - 1K Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | 1K ohm Carbon Film Resistors are typical axial-lead resistors, which have much better temperature stability and provide lower noise, and are generally better for high frequency or radiofrequency applications. | Series: - Resistance (Ohm): 1k Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | carbon film • 0.25w • passive • 1k resistor |
|  | EDR-00001-1M00 | 0.25W Resistor - 1M Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | It is a 1M Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications. | Series: - Resistance (Ohm): 1M Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | 0.25w • passive • 1m resistor • metal film |
|  | EDR-00001-220Z | 0.25W Resistor - 220 Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | It is a 220 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications. | Series: - Resistance (Ohm): 220 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | |
|  | EDR-00001-330Z | 0.25W Resistor - 330 Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | It is a 330 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications. | Series: - Resistance (Ohm): 330 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | |
|  | EDR-00001-470Z | 0.25W Resistor - 470 Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | It is a 470 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications. | Power: 1/4 W Resistance: 47k ? Resistance Tolerance: 5% Type: Carbon Film Resistors | resistor • carbon film • 0.25w • passive • axial • 470ohm |
|  | EDR-00001-680Z | 0.25W Resistor - 680 Ohm | CO - Consumables | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | It is a 680 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications. | Series: - Resistance (Ohm): 680 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | resistor • carbon film • 0.25w • passive • axial • 680ohm |