

Parts Export

Generated: 2026-06-10 09:00:55

Total Parts: 3

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EMC-00002-A	ESP8266 wifi module	EM - Electronic-Electrical Modules	Espressif Systems, Ai-Thinker, SparkFun	The ESP8266 WiFi Module is a low-cost microcontroller with built-in WiFi capability used for IoT (Internet of Things) applications. It allows devices to connect to WiFi networks and communicate with servers, cloud platforms, or mobile apps.	Product Type: WiFi Microcontroller Module Core Chip: ESP8266EX CPU: 32-bit Tensilica L106 Operating Voltage: 3.3V	ESP8266 WiFi Module • ESP8266 NodeMCU • ESP8266 ESP-01 • WiFi IoT Module • Arduino WiFi Module • ESP8266 Wireless Module • ESP8266 ESP-12E • ESP8266 IoT Board
No Image	EMC-00003-A	NodeMcu	EM - Electronic-Electrical Modules	Espressif Systems, Ai-Thinker, NodeMCU	The ESP8266 NodeMCU CH340 board has ESP8266 which is a highly integrated chip designed for the needs of a new connected world. It offers a complete and self-contained Wi-Fi networking solution, allowing it to either host the application or to offload all Wi-Fi networking functions from another application processor. ESP8266 has powerful on-board processing and storage capabilities that allow it to be integrated with the sensors and other application-specific devices through its GPIOs with minimal development up-front and minimal loading during runtime. Its high degree of on-chip integration allows for minimal external circuitry, and the entire solution, including the front-end module, is designed to occupy minimal PCB area. The ESP-12 Lua NodeMCU WIFI Dev Board Internet Of Things with ESP8266 is an all-in-one microcontroller + WiFi platform that is very easy to use to create projects with WiFi and IoT (Internet of Things) applications.	Processor: L106 32 bit Processor speed: 80MHz to 160MHz Flash memory: 4MB Analog to digital: 1 input with 1024 resolution Maximum concurrent TCP connection: 5 GPIOs: 17 Transfer rate: 110 Kbps to 460800 Kbps Input voltage supply: 4.5V to 9V Communication interface voltage: 3.3V Current consumption: 10uA-170mA	NodeMCU • ESP8266 • WiFi Module • IoT Development Board • ESP8266EX • Wireless Module
No Image	EMC-00005-A	RFID READER MODULE	EM - Electronic-Electrical Modules	NXP Semiconductors, Ai-Thinker, SunFounder, Keyestudio, Waveshare	RC522 - RFID Reader /Writer with Cards Kit includes a 13.56MHz RF reader and writer module that uses an RC522 IC and two S50 RFID cards tag. The MF RC522 is an integrated transmission module for contactless communication at 13.56 MHz. RC522 supports ISO 14443A/MIFARE mode. RC522 - RFID Reader features an outstanding modulation and demodulation algorithm to serve effortless RF communication at 13.56 MHz. The S50 RFID Cards will ease up the process helping you to learn and add the 13.56 MHz RF transition to your project. The module uses SPI to communicate with microcontrollers. The open-hardware community already has a lot of projects exploiting the RC522 – RFID Communication, using Arduino.	Operating Frequency (MHz): 13.56 Reading Distance (m): 2 cm to 5 cm Supply Voltage (V): 3.3V Operating Current (mA): 13 ~ 26 SPI data rate (Mbit/s): 10 Length (mm): 60 Width (mm): 39.5 Weight (g): 20	RC522 • RFID Reader • NFC Module • MFRC522 • 13.56MHz RFID • Arduino RFID