

# Parts Export

Generated: 2026-06-10 07:45:18

Total Parts: 3

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	<b>EDM-00006-A</b>	Male Headers	ED - Electronic Device	Samtec, Amphenol, Harwin, TE Connectivity, Molex	This break-away header can be snapped between any pair of pins to created any length header.	Pitch Size: 2.54mm (0.1 Inch) Connector Type: Male Pin Header Number of Pins: 40 Pins Mounting Type: Through Hole Current Rating: 3A Typical	Male Header • Pin Header • PCB Connector • Arduino Header • Breakaway Header • 2.54mm Header
No Image	<b>EDM-00007-A</b>	Female Headers	ED - Electronic Device	Samtec, Amphenol, Harwin, TE Connectivity, Molex	It is a 2x40 Pin Female Double Row Header Strip. It has two rows of 40 pins each. Ideal for through-hole mounting.	Pitch Size: 2.54mm (0.1 Inch) Connector Type: Female Header Socket Number of Pins: 40 Pins Mounting Type: Through Hole Current Rating: 3A Typical	PCB Connector • 2.54mm Header • Female Header • Socket Header • Arduino Connector • Female Pin Header
No Image	<b>EDM-00008-A</b>	Telephone Connector Adapter (Female)	ED - Electronic Device	Amphenol, TE Connectivity, Molex	RJ-11 4P4C female connector adapter designed for telephone communication interfaces, modular wiring systems, and embedded electronics applications. It allows easy plug-in connection for telephone cables, modem lines, and low-speed communication signals. Commonly used in landline telephone systems, DSL modems, intercom setups, IoT communication experiments, and electronics prototyping.	Connector Type: RJ-11 4P4C Female Jack Number of Contacts: 4 Pin (4P4C) Material: Thermoplastic Housing with Metal Contacts Rated Voltage: Low Voltage Signal (	RJ11 connector • 4P4C female jack • telephone adapter • modular connector • communication jack