

Parts Export

Generated: 2026-06-13 14:36:20

Total Parts: 25

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	COC-00004-A	Desoldering Wick	CO - Consumables	Generic	Finely braided 100% copper wick for fast and clean solder removal from electronic joints. Works with a heated soldering iron; flux-assisted for efficient molten solder absorption. Essential for PCB repair, rework, and general electronics maintenance tasks.	Item Type: Desoldering Wick Material: Suitable for Comfortable Desoldering Length: 1.5 m Width: 1.85 mm Thickness: Suitable for Comfortable Desoldering Application: Faster & Cleaner Electronics Desoldering Shipping Weight: 0.008 kg Shipping Dimensions (L x W x H): 6 x 5 x 1 cm	Desoldering Wick • Solder Braid • PCB Repair • 100% Copper • Solder Removal • Flux-Assisted • Electronics Rework • 1.5m
No Image	EDD-00001-A	Laser Diode	ED - Electronic Device	OSRAM, Sharp, Rohm, Mitsubishi, Generic	Mini 650nm 6mm 5mW Laser Dot Diode Module which is made of copper plastic. Can be driven from 3V to 5V DC so they're great for your embedded electronics project, robot, or other application. You require a 3 to 5VDC power supply which you'd get from two standard AAA or AA batteries. These diodes are 5mW output and have a safety label marked on them. It is suitable for 3V 5mW standard, with 6mm outside diameter, can be used to connect diode tubes for multiple uses.	Item Type: Laser Module Voltage Rating (V): 5 Weight (g): 2 Operating Temperature (°C): -10 to 50 Rated Power (mW): 5mW Wavelength (nm): 650	laser diode • laser • light emitter • optical • semiconductor • electronic device
No Image	EDD-00002-A	Red LED	ED - Electronic Device	Generic	Red Light Emitting Diode (LED) used as a visual indicator in electronic circuits and projects. Features a 10mm DIP package that emits bright red light with low power consumption and long operating life. Ideal for TVs, monitors, telephones, computers, status indicators, prototyping, educational experiments, DIY electronics, and general-purpose electronic applications.	Case/Package: DIP Diameter (mm): 10 Mounting Type: Through Hole Lens Appearance: Transparent Color: Red Forward Voltage (V): 2 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Red LED • Indicator LED • Through Hole LED • DIP LED • 10mm LED
No Image	EDD-00002-B	Green LED	ED - Electronic Device	Generic	Green Light Emitting Diode (LED) used as a visual indicator in electronic circuits and projects. Features a 3mm round transparent package that emits bright green light with low power consumption and long service life. Ideal for TVs, monitors, telephones, status indicators, DIY electronics, prototyping, educational experiments, and general-purpose electronic applications.	Case/Package: DIP Diameter (mm): 8 Mounting Type: Through Hole Lens Appearance: Transparent Color: Green Forward Voltage (V): 3.5 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Indicator LED • Through Hole LED • DIP LED • Green LED • 8mm LED
No Image	EDD-00002-C	Yellow LED	ED - Electronic Device	Generic	Yellow Light Emitting Diode (LED) used as a visual indicator in electronic circuits and projects. Features a 10mm DIP package with a transparent body that emits bright yellow light. Ideal for TVs, monitors, telephones, computers, status indicators, control panels, prototyping, educational experiments, DIY electronics, and general-purpose electronic applications.	Case/Package: DIP Diameter (mm): 10 Mounting Type: Through Hole Lens Appearance: Transparent Color: Yellow Forward Voltage (V): 3.2 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Indicator LED • Through Hole LED • DIP LED • 10mm LED • Yellow LED
No Image	EDD-00002-D	Blue LED	ED - Electronic Device	Generic	Blue Light Emitting Diode (LED) used as a visual indicator in electronic circuits and projects. Features a 3mm round transparent package that emits bright blue light with low power consumption and long operating life. Ideal for TVs, monitors, telephones, computers, DIY electronics, prototyping, educational experiments, and professional applications.	Mounting Type: Through Hole Through Hole LED Size (mm): 3 No. of Pins: 2 Color: Blue Head Shape: Round Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Indicator LED • Through Hole LED • 3mm LED • DIP LED • Blue LED • Round LED
No Image	EDK-00002-A	Ceramic capacitor	ED - Electronic Device	Generic, Murata, TDK, KEMET	A capacitor is a passive two-terminal electrical component used to store energy electrostatically in an electric field. It includes 20 capacitor values, 5 pieces of each type with a total of 100 capacitors.	Quantity: 100pcs (5 each per Value) Voltage: 50V	Electronics • passive • capacitor • ceramic • capacitor set

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EDK-00004-A	Metal Film Resistor Assorted Kit	ED - Electronic Device	Generic	Assorted kit of 600 metal film resistors with 30 different values, 20 pcs each. 1/4W, 1% tolerance resistors suitable for precise electronic, DIY, and educational projects.	Manufacturer: Generic Model Name: 600 pcs. Metal Film Resistor Assorted kit – 30 Kinds Power Rating: 1/4W Tolerance (%): 1 Material Type: Metal Film Package Type: Axial Lead Temperature Stability: High (Better than Carbon Film) Noise Level: Low Frequency Suitability: Suitable for RF and High-Frequency Applications Number of Values: 30 Total Quantity: 600 pcs Quantity per Value: 20 pcs Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Ideal for prototyping • learning resistor color codes • testing • and circuit experiments.
No Image	EDM-00005-B	Breadboard Mini	ED - Electronic Device	BusBoard Prototype, Twin Industries, Elegoo, SunFounder, Generic	Material: ABS Mini Solderless Breadboard Tie-point: 170 Completely reusable Colored coordinates for easy component placement Size: 45x34x9mm (1.771.34x0.35 inch) Color: Red, Black, White, Blue, Green	Item Type: Breadboard No. of Points: 170 Tie Points: 170 Material: ABS Mounting holes: M2 Length (mm): 48 Width (mm): 35 Height (mm): 9 Weight (g): 14	testing • Prototyping • Electronics • breadboard • mini breadboard • pcb • solderless
No Image	EDM-00005-C	Full-size breadboard	ED - Electronic Device	BusBoard Prototype, Twin Industries, Elegoo, SunFounder, Generic	An MB102 830 Points Solderless Prototype PCB Breadboard High Quality is an invaluable tool for experimenting with circuit designs whether in the R&D or university lab. A MB102 830 Points Solderless Prototype PCB Breadboard High Quality is used to make up temporary circuits for testing or to try out an idea. No soldering is required so it is easy to change connections and replace components.	Item Type: Breadboard, Solderless Type No. of Points: 830 Material: ABS	testing • Prototyping • Electronics • breadboard • pcb • solderless • full size breadboard
No Image	EDM-00005-D	PROTOTYPING SHIELD	ED - Electronic Device	Arduino, Keyes, DFRobot, Seeed Studio, Generic	Arduino Uno Protoshield directly fits into an Arduino UNO board and breaks out the I/O pins and makes it an expansion board. It makes it very easy to design any customer circuit. You can directly solder components on the board or connect the circuit using 170 point mini breadboard (included). The board is designed to solder both through-hole and SMD components to test them with your Arduino board. Although the SMD area is designed for 24 Pins SOIC integrated circuit and has a lot of space for TH components.	Breadboard Points: 170 Breadboard Size: 4.8x3.4 cm Shield Size: 7x5.4 cm	DIY • Electronics • pcb • arduino shield • prototyping shield • uno shield • development
No Image	EDR-00001-100Z	Resistor - 100 Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	1. 100 ohm Carbon Film Resistors are typical axial-lead resistors, which have much better temperature stability and provide lower noise, and are generally better for high frequency or radiofrequency applications. 2. We made it available in the form of a bunch of different values as required for the project to provide convenience, so you need not find a differently required value resistor at different places while working on your project.	Series: – Resistance (Ohm): 100 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	resistor • 100ohm • carbon film • passive component
No Image	EDR-00001-10K0	Resistor - 10K Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	1.10K/100? Carbon Film Resistors are typical axial-lead resistors that offer good temperature stability and low noise performance. They are suitable for general-purpose electronic circuits, including high-frequency and RF applications. 2. These resistors are available in multiple values for project flexibility, eliminating the need to source different resistor values separately.	Power: 1/4 W Resistance: 100 ? Resistance Tolerance: 5% Type: Carbon Film Resistors	Through Hole • carbon film • 10k resistor • 0.25w • passive • axial
No Image	EDR-00001-1K00	Resistor - 1K Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	1K ohm Carbon Film Resistors are typical axial-lead resistors, which have much better temperature stability and provide lower noise, and are generally better for high frequency or radiofrequency applications.	Series: – Resistance (Ohm): 1k Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	carbon film • 0.25w • passive • 1k resistor
No Image	EDR-00001-1M00	Resistor - 1M Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 1M Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: - Resistance (Ohm): 1M Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	0.25w • passive • 1m resistor • metal film

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EDR-00001-220Z	Resistor - 220 Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 220 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 220 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	
No Image	EDR-00001-330Z	Resistor - 330 Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 330 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 330 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	
No Image	EDR-00001-470Z	Resistor - 470 Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 470 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Power: 1/4 W Resistance: 47k ? Resistance Tolerance: 5% Type: Carbon Film Resistors	resistor • carbon film • 0.25w • passive • axial • 470ohm
No Image	EDR-00001-680Z	Resistor - 680 Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 680 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 680 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/-50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	resistor • carbon film • 0.25w • passive • axial • 680ohm
No Image	EDS-00006-A	IC NE 555	ED - Electronic Device	Texas Instruments, STMicroelectronics, ON Semiconductor, NXP, Generic	The NE 555 P timer IC is a precision timing circuit capable of producing accurate time delays or oscillation. In the time-delay or monostable mode of operation, the timed interval is controlled by a single external resistor and capacitor network. In the astable mode of operation, the frequency and duty cycle can be controlled independently with two external resistors and a single external capacitor. The threshold and trigger levels normally are two-thirds and one-third, respectively, of VCC. These levels can be altered by the use of the control voltage terminal. When the trigger input falls below the trigger level, the flip-flop is set, and the output goes high. If the trigger input is above the trigger level and the threshold input is above the threshold level, the flip-flop is reset and the output is low.	Case/Package: PDIP 8 Min Supply Voltage: 4.5 Max. Supply Voltage (V): 16 Product Type: Timers & Support Products Processor Series: NE555 No. of Timers/Counters: 1 Operating Temperature (°C): 0 to 70 Dimensions (L x W x H) mm: 9.81 x 4.57 x 6.35 Mounting Type: Through Hole	Electronics • ne555 • timer ic • oscillator • pulse generator • ic • astable
No Image	EDT-00007-A	Flex Sensor	ED - Electronic Device	Spectra Symbol, SparkFun, Adafruit, Interlink Electronics, Generic	A simple Flex Sensor 2.2? – Bend Sensor with a length of 2.2? which bends and flexes with a physical device. As the sensor is flex, the resistance across the sensor increases. A connector is 0.1? spaced and breadboard friendly. The flex sensor is a bend detecting sensor that has got numerous applications in Robotics, Gaming (Virtual Motion), Medical Devices, Computer Peripherals, Musical Instruments, Physical Therapy... The resistance of these sensors changes in accordance with the bend, which can be measured using any microcontroller.	Bend Resistance: minimum 20K Ohms ±30% (@ 180° pinch bend) Flat Resistance: 10K Ohms ±30% Flex length: 2.2 inch (5.6 cm) Power: 0.5 Watts continuous Length: 7 cm	Electronics • flex sensor • bend sensor • sensor • analog • resistance • wearable
No Image	EMA-00006-A	Buzzer module	EM - Electronic-Electrical Modules	Generic, Keyes, Elegoo, SunFounder, DFRobot	This is Small PCB Mountable 5V . It is great to add Audio Alert to your electronic designs. It operates on 5V supply, uses a coil element to generate an audible tone.	Voltage Rating: 5VDC Operating Voltage (VDC): 5 Pin Spacing (mm): 6 Material: Plastic Color: Black Width (mm): 12 (Body Diameter) Height (mm): 8 Weight (g): 1 (approx) (each) Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	buzzer • buzzer module • sound • alarm • electronic • module • 5v
No Image	EMA-00008-B	2 Channel Relay module	EM - Electronic-Electrical Modules	Songle, Keyes, SunFounder, Elegoo, Generic	This is a 5V 2 Channel Relay Module, be able to control various appliances, and other equipment with large current. It can be controlled directly by Microcontroller (8051, AVR, PIC, DSP, ARM, ARM, MSP430, TTL logic).5V 2-Channel Relay interface board and each one needs 15-20mA Driver Current Equipped with high-current relay, AC250V 10A; DC30V 10A Standard interface that can be controlled directly by microcontroller (8051, AVR, PIC, DSP, ARM, ARM, MSP430, TTL logic) Indication LED's for Relay output status.	No. of Channels: 2 Operating Temperature Range: -40 to 85 °C Operating Voltage: 2.5 ~ 5.5 V (DC) Switching Voltage(AC): 240V@10A Switching Voltage(DC): 30V@10A Trigger Current: 20 mA Trigger Voltage: 5V (DC) Length: 4.3 cm Height: 1.7 cm Width: 4.3 cm	arduino • module • 5v • relay module • 2 channel • switching • control

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	MMD-00002-B	Servo Motor	MM - Mechanical Module	TowerPro, MWduino Compatible, Generic	Compact 9g micro servo motor with 180° rotation for precise position control. Provides 1.2–1.6 kg-cm torque and fast response, making it ideal for robotics, RC models, automation, and educational projects. Compatible with Arduino and other microcontrollers using standard PWM signals. Lightweight, reliable, and easy to integrate into DIY and prototyping applications.	Item Type: TowerPro Servo Motor Model Series: SG Series Model No.: SG90 Rotation (Degree): 180° Torque Rating (kg-cm): 1.2 to 1.6 Operating Voltage (VDC): 3.0 – 7.2 Operating Speed @ 4.8V: 0.10 sec/60° Stall Torque @ 4.8V (kg-cm): 1.2 Stall Torque @ 6.6V (kg-cm): 1.6 Operating Temperature (°C): -30 to 60 Gear Type: Glass Fiber Servo Plug Type: JR Cable Length (cm): 25 Length (mm): 22.8 Width (mm): 12.6 Height (mm): 34.5 Weight (g): 9 Shipping Weight: 0.014 kg Shipping Dimensions (L x W x H): 8 x 6 x 4 cm	SG90 Servo • 9g Servo Motor • Micro Servo • RC Servo • Arduino Servo
No Image	MMK-00001-A	CABLES	MM - Mechanical Module	SparkFun, Adafruit, Pololu, Generic	Jumper wire cable set containing male-female, male-male, and female-female connection wires designed for breadboard prototyping, Arduino circuits, embedded systems, robotics, and electronics development applications. These cables provide reliable electrical connectivity, flexible routing, and easy plug-and-play interfacing between sensors, modules, microcontrollers, and development boards. Commonly used in DIY electronics, educational kits, IoT systems, PCB testing, and prototyping projects.	Cable Types: Male-Female, Male-Male, Female-Female Quantity: 80 MF, 80 MM, 80 FF Wire Length: 10cm – 30cm Conductor Material: Copper	Breadboard Wire • jumper wires • Dupont cable • MF cable • MM cable • FF cable