

Parts Export

Generated: 2026-06-10 07:20:24

Total Parts: 14

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EDT-00001-B	Gas Sensor Device	ED - Electronic Device	Hanwei Electronics, Winsen	Gas sensor device designed for detecting alcohol vapors and ethanol concentration in the air. It is commonly used for breath alcohol detection systems, safety monitoring, and embedded IoT applications. The sensor provides analog output based on gas concentration, making it suitable for microcontroller-based systems like Arduino and Raspberry Pi.	Sensor Type: Alcohol / Ethanol Gas Sensor Target Gas: Ethanol (C ₂ H ₅ OH), Alcohol Vapors Operating Voltage: 5V DC Warm-up Time: 20–48 hours (initial), few minutes per use	alcohol sensor • Gas Detector • ethanol sensor • MQ-3 sensor • breath alcohol sensor
No Image	EDT-00001-C	Gas Sensor Device	ED - Electronic Device	Hanwei Electronics, Winsen, Figaro Engineering	Gas sensor device designed for detecting methane (CH ₄), CNG, and natural gas leaks in the environment. It is widely used in safety monitoring systems, industrial gas leak detection, smart home safety devices, and IoT-based gas monitoring applications. The sensor provides analog output proportional to gas concentration, making it suitable for microcontroller-based systems like Arduino and embedded controllers.	Sensor Type: Methane / CNG Gas Sensor Target Gas: CH ₄ (Methane), CNG, Natural Gas Operating Voltage: 5V DC Warm-up Time: 20–60 seconds Detection Range: ~200–10000 ppm (typical)	methane sensor • CNG sensor • MQ-4 sensor • gas leak detector • natural gas sensor
No Image	EDT-00001-D	Gas Sensor Device	ED - Electronic Device	Hanwei Electronics, Winsen, Figaro Engineering	Gas sensor device designed for detecting LPG, propane, butane, smoke, and natural gas leaks in air safety and monitoring applications. It is widely used in gas leakage detection systems, smart home safety devices, industrial safety alarms, and IoT-based environmental monitoring systems.	Sensor Type: LPG / Natural Gas Sensor Target Gas: LPG (Propane, Butane), Natural Gas, Smoke Operating Voltage: 5V DC Warm-up Time: 20–60 seconds Detection Range: ~200–10000 ppm (typical)	MQ-2 Sensor • LPG Sensor • Propane Sensor • gas leak detector • natural gas sensor
No Image	EDT-00001-E	Gas Sensor Device	ED - Electronic Device	Hanwei Electronics, Winsen, Figaro Engineering	Gas sensor device designed for detecting LPG (liquefied petroleum gas), butane, and propane gas leaks in safety and monitoring applications. It is commonly used in gas leakage alarm systems, smart home safety devices, industrial safety monitoring, and IoT-based gas detection projects. The sensor provides analog output proportional to gas concentration, allowing easy interfacing with microcontrollers such as Arduino and embedded systems.	Sensor Type: LPG / Butane Gas Sensor Target Gas: LPG, Butane, Propane Operating Voltage: 5V DC Warm-up Time: 20–60 seconds Detection Range: ~200–10000 ppm (typical)	LPG Sensor • Propane Sensor • Butane Sensor • gas leak detector • MQ-6 sensor
No Image	EDT-00001-F	Gas Sensor Device	ED - Electronic Device	Hanwei Electronics, Winsen, Figaro Engineering	Gas sensor device designed for detecting carbon monoxide (CO), a highly toxic and odorless gas commonly produced by incomplete combustion. It is widely used in safety monitoring systems, industrial environments, smart home safety devices, and IoT-based air quality applications.	Sensor Type: Carbon Monoxide (CO) Gas Sensor Target Gas: CO (Carbon Monoxide) Operating Voltage: 5V DC Warm-up Time: 20–48 hours initial, few minutes per cycle Detection Range: ~20–2000 ppm (typical)	Carbon Monoxide Sensor • CO Sensor • Gas Detector • MQ-7 sensor • toxic gas sensor
No Image	EDT-00001-G	Gas Sensor Device	ED - Electronic Device	Winsen, Hanwei Electronics	Air quality device designed for detecting and monitoring harmful gases and air pollution levels in the environment. It measures gases such as CO, CO ₂ , smoke, LPG, methane, and other volatile compounds depending on the sensor type used. Commonly used in environmental monitoring systems, smart home automation, industrial safety systems, IoT air monitoring stations, and educational electronics projects.	Sensor Type: Multi-Gas Air Quality Sensor Device Detected Gases: CO, CO ₂ , Smoke, LPG, Methane, VOCs Operating Voltage: 5V DC Warm-up Time: 20–60 seconds	gas sensor • air quality device • pollution detector • MQ sensor • air monitoring system
No Image	EMS-00010-A	MQ-2 Gas Sensor Module- Methane, Butane, LPG, Smoke	EM - Electronic Modules	Hanwei Electronics, Winsen Electronics, SparkFun Electronics, DFRobot	The MQ-2 Gas Sensor Module is a semiconductor-based gas detection sensor designed to detect combustible and flammable gases such as Methane, Butane, LPG, Propane, Hydrogen, Alcohol, and Smoke. It uses a tin dioxide (SnO ₂) sensing layer whose resistance changes when exposed to combustible gases.	Product Type: Gas & Smoke Sensor Model: MQ-2 Detectable Gases: LPG, Methane, Butane, Smoke Detection Range: 200 – 10000 ppm Operating Voltage: 5V DC	LPG Gas Sensor • methane sensor • Arduino Gas Sensor • MQ-2 Gas Sensor • Smoke Sensor Module • Butane Gas Detector • MQ2 Smoke Detector • Flammable Gas Sensor

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EMS-00010-B	Alcohol Gas Sensor Module	EM - Electronic-Electrical Modules	Hanwei Electronics, Winsen Electronics, Waveshare	MQ-3 Alcohol Gas Sensor Module is used to detect alcohol concentration in the air and provides both analog and digital outputs. The module is based on the MQ-3 gas sensor which uses SnO ₂ (Tin Dioxide) sensing material. The sensor operates from 2.5V to 5V and includes an onboard potentiometer to adjust the digital output threshold level.	Operating Voltage (V): 2.5 to 5 Additional Specs: Output Pin: Analog and digital, Gold pin connectors, 2.54 mm pitch, Boost Converter Chip: PT1301 Board Size (mm): 40 x 21 mm Mounting Hole Diameter (mm): 2 mm Interface: Digital Output, Analog output, VCC Positive power supply (2.5V-5.0V), Power ground	arduino • alcohol sensor • MQ-3 • gas sensor • ethanol detector
No Image	EMS-00010-C	Methane and Natural Gas sensor	EM - Electronic-Electrical Modules	Hanwei Electronics, Winsen Electronics, Waveshare	MQ-4 Gas Sensor Module is a high sensitivity gas detection module used for sensing Methane (CH ₄), CNG, and natural gas leakage in the environment. An onboard potentiometer allows adjustment of the gas detection threshold level for digital output triggering. MQ-4 sensor is widely used in gas leakage alarms, industrial safety systems, and smart monitoring projects.	Model: MQ-4 Detecting range: 200 to 10000 ppm. Operating Voltage: 3 ~ 5 V Length: 3.1 cm Height: 2.1 cm Width: 1.9 cm	Arduino Compatible • gas sensor • MQ-4 • methane sensor • CNG detector
No Image	EMS-00010-D	Natural Gas and LPG Analog Sensor	EM - Electronic-Electrical Modules	Hanwei Electronics, Winsen Electronics, Waveshare	The MQ-5 is used in gas leakage detecting equipment in consumer and industry applications, this sensor is suitable for detecting LPG, natural gas, coal gas. Avoid the noise of alcohol, cooking fumes, and cigarette smoke. The sensitivity can be adjusted by the potentiometer. The sensitive material of the MQ-5 gas sensor is SnO ₂ , which with lower conductivity in clean air. When the target combustible gas exists, The sensor's conductivity is higher along with the gas concentration rising. Please use a simple electro circuit, Convert change of conductivity to the corresponding output signal of gas concentration. The sensor could be used to detect different combustible gas especially Methane, it is with low cost and suitable for different application	Model: MQ-5 Operating Temperature Range: -20 to 40 °C Operating Voltage: 5 V Length: 3.2 cm Height: 2.2 cm Width: 2 cm	Arduino Compatible • gas sensor • methane sensor • CNG detector • CH4 sensor
No Image	EMS-00010-E	Flammable Gas Sensor	EM - Electronic-Electrical Modules	Hanwei Electronics, Zhengzhou Winsen Electronics, DFRobot	This is a simple-to-use MQ-6 Liquefied Petroleum Isobutane Propane Gas Sensor module, suitable for sensing LPG (composed of mostly propane and butane) concentrations in the air. The MQ-6 can detect gas concentrations anywhere from 200 to 10000ppm. This sensor has high sensitivity and fast response time. The sensor's output is an analog resistance. The drive circuit is very simple; all you need to do is power the heater coil with 5V, add a load resistance, and connect the output to an ADC. The sensitive material of the MQ-6 gas sensor is SnO ₂ , which with lower conductivity in clean air. When the target combustible gas exists, The sensor's conductivity is higher along with the gas concentration rising. Please use a simple electro circuit, Convert change of conductivity to the corresponding output signal of gas concentration.	Model: MQ-6 Operating Temperature Range: -20 to 40 °C Operating Voltage: 5 V Length: 3.2 cm Height: 2.2 cm Width: 2 cm	arduino • gas sensor • methane sensor • MQ6 • LPG Sensor • Propane Sensor • Butane Sensor
No Image	EMS-00010-F	MQ-7 sensor module	EM - Electronic-Electrical Modules	Hanwei Electronics, Zhengzhou Winsen Electronics, DFRobot	This MQ7 Carbon Monoxide Gas Sensor Module is a semiconductor gas sensor tuned to detect carbon monoxide. It is in the same family of devices as the smoke detector sensor, measuring the change in surface conductivity of tin dioxide in the presence of carbon monoxide. This sensor has high sensitivity and fast response time. The sensor can measure concentrations of 10 to 10,000 ppm. The sensor can operate at temperatures from -10 to 50°C and consumes less than 150 mA at 5 V. This module provides both digital and analog outputs. The threshold level for digital output can be easily adjusted using the preset on the board. The MQ-7 sensor module can be easily interfaced with Micro-controllers, Arduino and etc.	Model: MQ-7 Ambient temperature: -20 ~ + 50 °C Characteristic gas: 100 ppm CO Heating current: ? 180 mA Heating power: approx. 350 mW Heating resistance: ± 31 ? Heating voltage: 5.0V ± 2V / 1.5 ± 1V Humidity: ? 95% RH Operating Voltage: 5 V Oxygen content: 21%. Range: 10 ~ 1000 ppm Return time: ? 30 s Sensitivity: ? 3%. Length: 3.5 cm Height: 1.1 cm Width: 2 cm	arduino • MQ7 • Carbon Monoxide Sensor • CO Sensor • Gas Detector • Air Quality Sensor
No Image	EMS-00010-G	MQ135 gas sensor	EM - Electronic-Electrical Modules	Hanwei Electronics, Zhengzhou Winsen Electronics, Futurlec	The MQ 135 Air Quality Detector Sensor Module For Arduino has lower conductivity in clean air. When the target combustible gas exists, the conductivity of the sensor is higher along with the gas concentration rising. Convert change of conductivity to the corresponding output signal of gas concentration. The MQ135 gas sensor has a high sensitivity to Ammonia, Sulphide, and Benzene steam, also sensitive to smoke and other harmful gases. It is at low cost and suitable for different applications such as harmful gases/smoke detection.	Model: MQ-135 Detecting range: 100ppm to 1000ppm Operating current: 150 mA Operating Voltage: 5 V Length: 3.2 cm Height: 2.7 cm Width: 2 cm	Air Quality Sensor • MQ135 • Ammonia Sensor • NOx Sensor • CO2 Sensor • Smoke Sensor
No Image	EMS-00010-H	Hydrogen Gas Sensor - MQ-8 - SEN-10916	EM - Electronic-Electrical Modules	SparkFun Electronics, Hanwei Electronics, Winsen Electronics, SparkFun	The MQ-8 Hydrogen Gas Sensor is a semiconductor-based gas detection sensor designed to detect hydrogen (H ₂) gas concentration in air. It is highly sensitive to hydrogen and can detect gas concentrations ranging from 100 ppm to 10,000 ppm. The sensor uses a tin dioxide (SnO ₂) sensing layer whose resistance changes when exposed to hydrogen gas. The module provides both analog and digital outputs, making it easy to interface with Arduino, ESP32, Raspberry Pi, STM32, and other microcontrollers.	Product Type: Hydrogen Gas Sensor Model: MQ-8 SparkFun SKU: SEN-10916 Detectable Gas: Hydrogen (H ₂) Detection Range: 100 – 10,000 ppm Operating Voltage: 5V DC	MQ-8 Gas Sensor • Hydrogen Gas Sensor • H2 Gas Detector • MQ8 Sensor Module • Hydrogen Detection Sensor • Arduino Gas Sensor • ESP32 Hydrogen Sensor • Gas Leakage Sensor