

Parts Export

Generated: 2026-06-13 13:17:18

Total Parts: 2

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EMC-00006-B	GSM-GPRS Module (SIM900A)	EM - Electronic-Electrical Modules	SIMCom, DFRobot, Itead Studio	The onboard two set power supply interface VCC5 5V power supply, VCC4 interface, 3.5--4.5V power supply, optional power on self-starting (default), and control start. The onboard SMA (default) and IPXmini antenna interface, SIM900A interface reserved reset. The size of the module is 49*50, all the new and original device. The computer can give early computer debugging USB module power supply, a very large amount of data under the condition of the recommended current more than 1A. Standby dozens of MA data can be set to provide dormancy, dormancy of 10MA low power. Support 2, mobile phone 3,4G card. The serial port circuit: support for 3.3V single-chip microcomputer. TTL serial port support 3.3 and 5V single-chip microcomputer. The SIM card circuit to increase the SMF05C ESD chip. Antenna circuit: guarantee short and straight, so as to ensure the signal strength. PCB display screen printing mark: each interface, convenient development two times, the SIM900/A hardware completely follows the design when the design manual.	Frequency bands: Dual-band GPRS connectivity: GPRS multi-slot class 10 (default) , GPRS multi-slot class 8 (option) Operating Temperature Range: -30 to 80 °C Supply Voltage: 3.4 – 4.5 V Dimensions (LxWxH): 8.5x5.7x2cm (approx)	GSM Module • GPRS Module • SMS Module • IoT Module • Arduino GSM • SIM900A
No Image	EMS-00026-A	HMC5883L Triple Axis Compass Magnetometer Sensor Module	EM - Electronic-Electrical Modules	Honeywell, ITEAD Studio, DFRobot, Adafruit, SparkFun	HMC5883L Triple Axis Compass Magnetometer Sensor Module is a 3-axis digital compass sensor used for navigation, heading detection, robotics, drones, GPS systems, and Arduino projects. The module communicates through the I2C interface and measures magnetic field strength across X, Y, and Z axes for accurate compass heading and orientation detection.	Product Type: Triple Axis Magnetometer Sensor Model: HMC5883L Number of Axes: 3 Axis Communication Interface: I2C Operating Voltage: 3.3V – 5V ADC Resolution: 12-bit	HMC5883L Sensor • Magnetometer Module • Compass Sensor • Triple Axis Compass • GY-271 Sensor • GY-273 Module • Arduino Compass Sensor