

Parts Export

Generated: 2026-06-10 08:00:45

Total Parts: 4

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|----------|--------------------|----------------------------|------------------------------------|---|---|---|---|
| No Image | EDM-00005-A | 400 Pin Breadboard | ED - Electronic Device | MWduino / Generic | Complete prototyping kit with 400-point solderless breadboard and T-type GPIO breakout module. Includes 40-pin flat ribbon cable for clean and organized Raspberry Pi GPIO access. Ideal for Raspberry Pi projects, circuit prototyping, and educational experimentation. | Item Type: Cable Model: GPIO Compatibility: Raspberry Pi 3 Model B/B+ T: Connector Dimensions (mm): 72 x 59 x 12 T: Connector Weight (g): 13 Pitch (mm): 2.54 Cable Length (cm): 20 (Flat Ribbon) No. of Pins: 40 Width of Cable (cm): 5.5 Additional Specs (mm): 84 x 55 x 8.5 (L x W x H) No. of Tie Points: 400 Weight (g): 40 Material: ABS Plastic Shipping Weight: 0.06 kg Shipping Dimensions (L x W x H): 10 x 7 x 7 cm | Breadboard 400 Point • GPIO Breakout Board • Raspberry Pi GPIO • T-Type Adapter • 40 Pin Ribbon Cable |
| No Image | EMA-00001-A | I2C LCD | EM - Electronic-Electrical Modules | MWduino / Generic, KEYESTUDIO, SunFounder | 16x2 character LCD module with integrated I2C interface for simplified wiring. Blue backlight with white characters for clear and high-contrast visibility. Ideal for Arduino, Raspberry Pi, and embedded systems requiring compact data display. | Model: Other LCD Model No.: LCD1602 Display Type: 16 x 2 Character LCD Backlight Color: Blue Character Color: White I2C Address: 0x27 Input Voltage (V): 5 Length (mm): 36 Width (mm): 80 Height (mm): 18 Weight (g): 35 Shipping Weight: 0.037 kg Shipping Dimensions (L x W x H): 8 x 5 x 3 cm | LCD1602 • 16x2 LCD • I2C LCD Display • Arduino Display • Character LCD Module |
| No Image | EMS-00005-A | Ultrasonic Distance Sensor | EM - Electronic-Electrical Modules | MWduino / Generic, ElecFreaks, KEYESTUDIO, SunFounder | Ultrasonic distance sensor module using 40kHz sound waves for accurate measurement. Operates on 3.3–5.5V DC with 4-pin interface (VCC, Trig, Echo, GND). Ideal for robotics, obstacle detection, automation, and distance sensing projects. | Power Supply (V): +5V DC Working Current (mA): 15 mA Output Signal: Electrical frequency signal Ranging Distance: 2 cm – 400 cm Distance Resolution: 0.3 cm Measuring Angle: 30° Operating Voltage Range (V): 3.3V – 5.5V Interface Type: 4-pin (VCC, Trig, Echo, GND) Shipping Weight: 0.007 kg Shipping Dimensions (L x W x H): 9 x 6 x 2 cm | Ultrasonic Sensor • HC-SR04+ • Distance Sensor • Arduino Sensor • Obstacle Detection Module |
| No Image | MMC-0000Y-A | Male-to-Female Jumper Wire | MM - Mechanical Module | MWduino / Generic | 20 cm male-to-female jumper wires for flexible and reliable circuit connections. Includes 20 multi-color wires with 2.54mm male pins and female header connectors. Ideal for Arduino, Raspberry Pi, sensors, and breadboard prototyping projects. | Item Type: Jumper Wire Cable Type: Male to Female Cable Length (cm): 20 Quantity (pcs): 20 Connector Type: Male Pin ? Female Header Color Coding: Multi-color (10–20 assorted colors) Compatibility: Breadboards, Arduino, Raspberry Pi, Sensors Weight (g): 16 Shipping Weight: 0.016 kg Shipping Dimensions (L x W x H): 10 x 7.5 x 2 cm | Breadboard Wire • Arduino Wire • Prototyping Cable • Jumper Wire • Male to Female |