

Parts Export

Generated: 2026-07-26 16:00:17

Total Parts: 17

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COE-00002-A	Hookup Wire Kit	CO - Consumables	Plusivo	The Assorted 30AWG Silicone Hookup Wire Kit is a flexible wiring set for electronics and prototyping. It includes multiple colored wires, heat shrink tubes, and accessories for easy circuit building. It is widely used in Arduino projects, robotics, and embedded system wiring.	Brand: Plusivo Item Type: Hookup Wire Kit Wire Gauge: 30 AWG Conductor Material: 0.08 mm Tinned Copper (Stranded) Insulation Material: Silicone Rated Voltage: 300 V Rated Temperature: 200°C Wire Length: 20 meters per color (6 colors) Total Wire Length: 120 meters Weight: 285 g Shipping Weight: 0.27 kg Shipping Dimensions (L × W × H): 15 × 7 × 7 cm	Hookup Wire • Silicone Wire • Stranded Wire • 30AWG • Prototyping • Electronics
	EDM-00001-A	Tactile Switch	ED - Electronic Device	OMRON, E-Switch	This tactile push button switch kit includes 12×12×7.3mm momentary ON-OFF switches for reliable circuit input. Rated for 12V DC and 120mA, they provide good tactile feedback. The kit includes 25 color-coded keycaps and a storage box, making it ideal for Arduino projects, prototyping, DIY electronics, and educational use.	Item Type: Micro Switch Model: Tactile Push Button Switch Operation Mode: ON-OFF Contact Type: Momentary Current Rating: 120mA Operating Voltage: 12V DC Switch Type: Push Button Material: Metal and Plastic Mounting Type: Surface Mount Button Size (mm): 12×12×7.3 Operating Temperature (°C): -25 to +70 Lifespan: ~1000 Cycles Box Dimensions (mm): 127.1 × 68.3 × 21.9 Weight (g): 55 Shipping Weight: 0.06 kg Shipping Dimensions (L × W × H): 13 × 7 × 3 cm	Tactile Switch • Push Button • 12x12mm Switch • Momentary Switch • Arduino Button Kit
	EDM-00005-A	Prototype Board	ED - Electronic Device	MWduino / Generic	Complete prototyping kit with 400-point solderless breadboard and T-type GPIO breakout module. Includes 40-pin flat ribbon cable for clean and organized Raspberry Pi GPIO access. Ideal for Raspberry Pi projects, circuit prototyping, and educational experimentation.	Item Type: Cable Model: GPIO Compatibility: Raspberry Pi 3 Model B/B+ T: Connector Dimensions (mm): 72 × 59 × 12 T: Connector Weight (g): 13 Pitch (mm): 2.54 Cable Length (cm): 20 (Flat Ribbon) No. of Pins: 40 Width of Cable (cm): 5.5 Additional Specs (mm): 84 × 55 × 8.5 (L × W × H) No. of Tie Points: 400 Weight (g): 40 Material: ABS Plastic Shipping Weight: 0.06 kg Shipping Dimensions (L × W × H): 10 × 7 × 7 cm	Breadboard 400 Point • GPIO Breakout Board • Raspberry Pi GPIO • T-Type Adapter • 40 Pin Ribbon Cable
No Image	EMA-00002-A	OLED Display	EM - Electronic-Electrical Modules	Solomon Systech, SparkFun, DFRobot	The SSD1306 0.96-inch I2C OLED Display is a compact monochrome graphical display module widely used with Arduino, ESP32, Raspberry Pi, and other microcontrollers. It features a 128×64 pixel resolution and uses the SSD1306 OLED driver IC with an I2C communication interface. The display provides high contrast, low power consumption, and is ideal for showing text, graphics, sensor data, and menus.	Product Type: OLED Display Module Display Size: 0.96 inch Driver IC: SSD1306 Resolution: 128 × 64 Pixels Operating Voltage: 3.3V – 5V DC	SSD1306 OLED Display • 0.96 OLED Module • I2C OLED Display • OLED Screen Module
No Image	EMA-00003-B	RGB NeoPixel 8 LED	EM - Electronic-Electrical Modules	Worldsemi Co., Ltd., Generic / OEM	The WS2812B 8-Bit RGB LED Module features 8 individually addressable 5050 RGB LEDs with built-in driver ICs for precise color and brightness control. Operating on 5V and using a single-wire communication protocol, it enables vibrant lighting effects and animations with minimal wiring. Ideal for Arduino projects, IoT devices, decorative lighting, displays, and interactive electronic creations.	LED Model: WS2812B Package Type: 5050 SMD Number of LEDs: 8 Color Type: Full-Color RGB Bit Depth: 8-bit per channel (24-bit RGB total) Operating Voltage: DC 5V Control Interface: Single Data Line (Serial) Communication Protocol: One-Wire Timing Protocol PCB Color: White Mounting Type: Solderless / Plug-and-Play Length (mm): 105 Width (mm): 10 Height (mm): 6 Weight (g): 8 Shipping Weight: 0.01 kg Shipping Dimensions (L × W × H cm): 12 × 8 × 1	Arduino Compatible • WS2812B • NeoPixel Module • 8 LED RGB • 5050 SMD • Addressable LED • 5V RGB Strip • Programmable LED
No Image	EMA-00006-A	Buzzer module	EM - Electronic-Electrical Modules	Generic, Keyes, Elegoo, SunFounder, DFRobot	The Small PCB Mountable 5V Buzzer is an audio alert component used to produce sound in electronic circuits. It operates on 5V DC and is commonly used in alarms, timers, Arduino projects, and embedded systems for simple audio feedback and notifications.	Voltage Rating: 5VDC Operating Voltage (VDC): 5 Pin Spacing (mm): 6 Material: Plastic Color: Black Width (mm): 12 (Body Diameter) Height (mm): 8 Weight (g): 1 (approx) (each) Shipping Weight: 0.001 kg Shipping Dimensions: 1 × 1 × 1 cm	buzzer • buzzer module • sound • alarm • electronic • module • 5v

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EMA-00008-A	1 Channel Relay	EM - Electronic-Electrical Modules	Single Relay, Generic / OEM	The Single Channel 12V Relay Module is used to control high-voltage AC/DC devices using low-voltage microcontrollers. It supports high/low-level triggering and includes LED indicators. It is commonly used in home automation, IoT, and motor control applications.	Model: Relay Module Number of Channels: 1 Operating Voltage (VDC): 12 Trigger Type: High-Level / Low-Level Trigger Relay Contact Rating (AC): 10A @ 250V AC Relay Contact Rating (AC Alternate): 15A @ 125V AC Contact Type: COM, NO (Normally Open), NC (Normally Closed) Interface: 2.54 mm Header Pins Output Connection: 3-Pin Screw Terminal Indicators: Power LED + Relay Status LED Length (mm): 50 Width (mm): 25 Height (mm): 20 Weight (g): 16 Shipping Weight: 0.025 kg Shipping Dimensions (L × W × H cm): 7 × 4 × 3	Arduino Compatible • 12V Relay Module • Single Channel Relay • High/Low Trigger • Sngle SRD-12VDC-SL-C • SPDT Relay • 10A 250VAC • IoT Switching Module
No Image	EMC-00006-B	GSM Module	EM - Electronic-Electrical Modules	SIMCom, DFRobot, Itead Studio	The SIM900A GSM Module is a wireless communication module used for SMS, voice, and data applications over GSM networks. It supports UART communication and SIM card integration for microcontrollers like Arduino. It is widely used in IoT systems, remote monitoring, automation, and embedded communication projects.	Frequency bands: Dual-band GPRS connectivity: GPRS multi-slot class 10 (default) , GPRS multi-slot class 8 (option) Operating Temperature Range: -30 to 80 °C Supply Voltage: 3.4 – 4.5 V Dimensions (LxWxH): 8.5x5.7x2cm (approx)	GSM Module • GPRS Module • SMS Module • IoT Module • Arduino GSM • SIM900A
	EMS-00001-A	MQ-2 Gas Sensor	EM - Electronic-Electrical Modules	Hanwei Electronics Group Corporation, Zhengzhou Winsen Electronics Technology Co., Ltd.	The MQ-2 Gas Sensor Module detects combustible gases such as LPG, methane, hydrogen, alcohol vapor, and smoke. It uses a SnO ₂ sensing element and provides both analog and digital outputs with adjustable sensitivity. Ideal for gas leakage detection, safety systems, fire alarms, environmental monitoring, smart home applications, and Arduino-based electronics projects.	Sensor Model: MQ-2 Detection Range: 300 – 10,000 ppm Detectable Gases: LPG, Butane, Propane, Methane (CH ₄), Hydrogen (H ₂), Alcohol, Smoke, CO Sensing Material: Tin Dioxide (SnO ₂) Operating Voltage: 5V DC Digital Output Voltage: 0V or 5V (TTL Logic) Analog Output: Yes Sensitivity Adjustment: Onboard Potentiometer Preheat Time: 20 seconds (minimum) Dimensions (mm): 36 × 20 × 21 Weight (g): 8 Shipping Weight: 0.012 kg Shipping Dimensions (cm): 4 × 4 × 4	Arduino Compatible • MQ-2 Sensor • LPG Gas Sensor • Smoke Detector • SnO ₂ Sensor • Combustible Gas Module • 5V Gas Sensor • Gas Leakage Detector
	EMS-00015-B	3x4 Membrane Keypad	EM - Electronic-Electrical Modules	Adafruit, DFRobot, SparkFun, Keyestudio	The 3x4 12-Key Membrane Keypad is a compact matrix input device used with Arduino, ESP32, Raspberry Pi, and other microcontrollers. It has 12 buttons in a 4x3 telephone-style layout, reducing GPIO usage while allowing easy user input. It is commonly used in password systems, calculators, access control, and embedded projects.	Product Type: Membrane Matrix Keypad Key Layout: 3x4 Matrix Number of Keys: 12 Operating Voltage: 3V – 35V DC Connector Type: 7-pin Header	12 Key Matrix Keypad • Membrane Switch Keypad • Arduino Keypad • 3x4 Membrane Keypad • Numeric Keypad Module • 4x3 Matrix Keyboard • Telephone Style Keypad • Matrix Input Module
	EMS-00015-C	4x4 Keypad	EM - Electronic-Electrical Modules	Adafruit, Keyestudio, DFRobot, SparkFun	The 4x4 / 4x3 Membrane Keypad is a thin, flexible input device used with Arduino, ESP32, Raspberry Pi, and other microcontrollers. It uses a row-column matrix to reduce GPIO usage while providing multiple button inputs. It is commonly used in password systems, calculators, access control, and embedded projects.	Product Type: Membrane Matrix Keypad Key Layout: 4x4 / 4x3 Number of Keys: 12 or 16 Operating Voltage: 3V – 35V DC Connector Type: 7-pin / 8-pin Header	4x4 Membrane Keypad • 12 Key Matrix Keypad • Membrane Switch Keypad • Matrix Keyboard Module • Arduino Keypad • Numeric Input Module • 4x3 Matrix Keypad • Keypad Module
	EMX-00001-A	Arduino Uno R3	EM - Electronic-Electrical Modules	Arduino, Elegoo, HiLetgo, Keyestudio	The Arduino Uno R3 is a microcontroller development board based on the ATmega328P, designed for building interactive electronics projects. It features 14 digital I/O pins, 6 analog inputs, a 16 MHz clock, USB interface, and operates at 5V. It is widely used in education, prototyping, robotics, and embedded system development.	Board Type: Uno With Cable: Yes Operating Voltage: 5 V Input Voltage Range: 6 – 20 V Analog I/O Pins: 6 Digital I/O Pins: 14 (6 × PWM) DC Current per I/O Pin: 40 mA Clock Speed: 16 MHz SRAM: 2 KB EEPROM: 1 KB Flash Memory: 32 KB Dimensions (L × W × H): 75 × 54 × 12 mm Weight: 28 g (without cable), 54 g (with cable)	ATmega328P • 5 V Board • 16 MHz Crystal • USB Interface • Microcontroller • Educational Kit • Open-Source Hardware • Breadboard Compatible
	EQE-00002-A	Digital Multimeter	EQ - Equipment/Instrument	Generic / OEM, YX-360, Mastech, Victor, Pro'sKit	Compact Digital Multimeter for everyday electrical testing. Measures AC/DC voltage, DC current, resistance, diode, continuity, transistor hFE, battery condition, and square wave output. Features an easy-to-read LCD display for accurate readings. Ideal for students, hobbyists, laboratories, DIY projects, and technicians for troubleshooting, testing, and educational applications.	Item Type: Multimeter Model Type: Digital Multimeter (DT830D Type) Probe Length: 60 cm Length: 120 mm Width: 70 mm Height: 27 mm Weight: 160 g Shipping Weight: 0.18 kg Shipping Dimensions: 15 × 8 × 3.5 cm	DT830D • Digital Multimeter • AC/DC Tester • LCD Display • VOM

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	MMD-00002-B	Servo Motor	MM - Mechanical Module	TowerPro, MWduino Compatible, Generic	Compact 9g micro servo motor with 180° rotation for precise position control. Provides 1.2–1.6 kg-cm torque and fast response, making it ideal for robotics, RC models, automation, and educational projects. Compatible with Arduino and other microcontrollers using standard PWM signals. Lightweight, reliable, and easy to integrate into DIY and prototyping applications.	Item Type: TowerPro Servo Motor Model Series: SG Series Model No.: SG90 Rotation (Degree): 180° Torque Rating (kg-cm): 1.2 to 1.6 Operating Voltage (VDC): 3.0 – 7.2 Operating Speed @ 4.8V: 0.10 sec/60° Stall Torque @ 4.8V (kg-cm): 1.2 Stall Torque @ 6.6V (kg-cm): 1.6 Operating Temperature (°C): -30 to 60 Gear Type: Glass Fiber Servo Plug Type: JR Cable Length (cm): 25 Length (mm): 22.8 Width (mm): 12.6 Height (mm): 34.5 Weight (g): 9 Shipping Weight: 0.014 kg Shipping Dimensions (L × W × H): 8 × 6 × 4 cm	SG90 Servo • 9g Servo Motor • Micro Servo • RC Servo • Arduino Servo
	MMP-00003-B	M3 Screw 12mm	MM - Mechanical Module	Unbrako, TVS Fasteners, Bossard, RS PRO	M3 × 12mm machine screws are metric fasteners used in PCB mounting, robotics, Arduino projects, 3D printing, electronics enclosures, and mechanical assemblies. They offer strong, precise, and reliable fastening and are available in stainless steel and alloy steel with Phillips, Allen, and hex head options. Ideal for prototyping, repairs, manufacturing, and DIY electronics applications.	Product Type: Machine Screw Screw Size: M3 × 12mm Thread Type: Metric Thread Application: PCB Mounting, DIY, Robotics	DIY Hardware • M3 Screw • Machine Screw • Hex Screw • Mounting Screw • PCB Screw • M3x12mm Screw
	TLC-00001-A	Cutting mat	TL - Tools	OLFA, Deli, Fiskars, Pro'sKit	An A2 cutting mat is a self-healing protective work surface used for cutting paper, vinyl, fabric, PCB sheets, foam, leather, and craft materials. It protects tables and blades while providing printed measurement grids for accurate cutting in DIY, electronics, art, and workshop applications.	Product Type: Self Healing Cutting Mat Size: A2 Dimensions: Approx. 600 × 450 mm Material: PVC Multi-layer Thickness: 2 mm – 3 mm	Cutting Mat • A2 Cutting Mat • Self Healing Mat • Craft Mat • DIY Cutting Board • Precision Cutting Mat • Workshop Mat
	TLC-00007-A	Desolder Pump	TL - Tools	Generic / OEM, Noel, Pro'sKit, Velleman, Engineer	A desoldering pump is a handy tool used to remove molten solder from PCBs during repairs and component replacement. It uses a spring-loaded plunger and heat-resistant nozzle to create strong suction, quickly clearing solder from joints. Lightweight, portable, and easy to use, it helps ensure clean desoldering while reducing the risk of damage to delicate electronic components.	Item Type: Desoldering Pump Body Material: Aluminum or Plastic Tip Material: Heat-resistant Teflon Color: Blue / Silver Length: 190 mm Width: 30 mm Height: 30 mm Weight: 29 g Shipping Weight: 0.03 kg Shipping Dimensions: 17 × 12 × 3 cm	PCB Rework • Desoldering Pump • Solder Sucker • Manual Vacuum • Teflon Tip