

Parts Export

Generated: 2026-06-10 10:49:28

Total Parts: 32

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|----------|-----------------------|--------------------------|------------------------|----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| No Image | COC-00006-A | Sandpaper | CO - Consumables | 3M, Norton Abrasives | Abrasive sandpaper sheet designed for surface smoothing, polishing, finishing, paint removal, and material preparation applications. It provides efficient abrasion for wood, plastic, metal, fiberglass, and fabrication materials while ensuring smooth finishing and surface cleaning. | Product Type: Abrasive Sandpaper Sheet Abrasive Material: Aluminum Oxide / Silicon Carbide Grit Range: 60 – 3000 Grit Sheet Size: Standard 9x11 Inch | sandpaper • abrasive paper • sanding sheet • polishing paper • surface finishing |
| No Image | EDD-00005-C | 6Volt regulator | ED - Electronic Device | Texas Instruments, STMicroelectronics, ON Semiconductor, Fairchild Semiconductor | LM7806 TO-92 voltage regulator device designed to provide stable 6V DC output for electronic circuits, embedded systems, sensors, and low-power applications. It regulates higher input voltage into a constant 6V output with built-in thermal overload and short-circuit protection for reliable and safe operation. Commonly used in Arduino projects, battery-powered systems, robotics circuits, educational electronics kits, and embedded development applications. | Device Type: Linear Voltage Regulator Output Voltage: 6V DC Package Type: TO-92 Input Voltage Range: 8V – 20V Output Current: Up to 100mA | voltage regulator • TO-92 regulator • linear regulator • power supply IC • LM7806 • 6V regulator |
| No Image | EDK-00006-A | Diode and Transistor Kit | ED - Electronic Device | ON Semiconductor, Vishay, STMicroelectronics, Fairchild Semiconductor | Diode and transistor kit containing a selection of commonly used semiconductor components including rectifier diodes, signal diodes, Zener diodes, NPN and PNP transistors for electronics prototyping and circuit development. It provides essential components for switching, signal control, rectification, voltage regulation, and amplification in embedded systems. | Kit Type: Semiconductor Assortment Kit Components Included: Diodes (Rectifier, Signal, Zener), NPN & PNP Transistors Max Voltage: Up to 1000V (depending on component) Max Current: Up to 3A (depending on component) | transistor kit • NPN transistor • semiconductor kit • diode kit • rectifier diode • Zener diode |
| No Image | EDM-00006-A | Male Headers | ED - Electronic Device | Samtec, Amphenol, Harwin, TE Connectivity, Molex | This break-away header can be snapped between any pair of pins to created any length header. | Pitch Size: 2.54mm (0.1 Inch) Connector Type: Male Pin Header Number of Pins: 40 Pins Mounting Type: Through Hole Current Rating: 3A Typical | Male Header • Pin Header • PCB Connector • Arduino Header • Breakaway Header • 2.54mm Header |
| No Image | EDM-00006-B | Headers | ED - Electronic Device | Molex, Harwin | 90 degree (right angle) header pins designed for PCB mounting and board-to-wire or board-to-board connections in electronic circuits. These connectors allow horizontal cable attachment, making them ideal for compact PCB layouts, Arduino shields, embedded systems, and robotics applications. | Connector Type: Right Angle Pin Header (90°) Pin Pitch: 2.54mm (Standard) Pin Count: 1x1 to multi-pin strips | Pin Header • PCB Connector • 90 degree header • right angle header • Arduino header pins |
| No Image | EDR-00001-680Z | Resistor - 680 Ohm | ED - Electronic Device | Yageo, Vishay, KOA Speer, TE Connectivity, Generic | It is a 680 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications. | Series: – Resistance (Ohm): 680 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | resistor • carbon film • 0.25w • passive • axial • 680ohm |
| No Image | EDS-00006-A | IC NE 555 | ED - Electronic Device | Texas Instruments, STMicroelectronics, ON Semiconductor, NXP, Generic | The NE 555 P timer IC is a precision timing circuit capable of producing accurate time delays or oscillation. In the time-delay or monostable mode of operation, the timed interval is controlled by a single external resistor and capacitor network. In the astable mode of operation, the frequency and duty cycle can be controlled independently with two external resistors and a single external capacitor. The threshold and trigger levels normally are two-thirds and one-third, respectively, of VCC. These levels can be altered by the use of the control voltage terminal. When the trigger input falls below the trigger level, the flip-flop is set, and the output goes high. If the trigger input is above the trigger level and the threshold input is above the threshold level, the flip-flop is reset and the output is low. | Case/Package: PDIP 8 Min Supply Voltage: 4.5 Max. Supply Voltage (V): 16 Product Type: Timers & Support Products Processor Series: NE555 No. of Timers/Counters: 1 Operating Temperature (°C): 0 to 70 Dimensions (L x W x H) mm: 9.81 x 4.57 x 6.35 Mounting Type: Through Hole | Electronics • ne555 • timer ic • oscillator • pulse generator • ic • astable |

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|----------|--------------------|------------------------------------|------------------------------------|--------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No Image | EDT-00006-A | Force Sensor - ROUND | EM - Electronic-Electrical Modules | Interlink Electronics, SparkFun Electronics, DFRobot, Adafruit Industries, Ohmite, Tekscan | This is a force sensitive resistor with a round, 0.5" diameter, sensing area. This FSR will vary its resistance depending on how much pressure is being applied to the sensing area. The harder the force, the lower the resistance. When no pressure is being applied to the FSR its resistance will be larger than 1M?. This FSR can sense applied force anywhere in the range of 100g-10kg. Two pins extend from the bottom of the sensor with a 0.1" pitch making it bread friendly. There is a peel-and-stick rubber backing on the other side of the sensing area to mount the FSR. Just Connect a resistor to form a voltage divider and measure the voltage at the junction to find the force applied. This sensor can be easily interfaced with Microcontrollers, Arduino Boards, Raspberry Pi, etc. using an Analog to Digital Converter (ADC). | Diameter: 1.8 cm Max Pressure: 10 Kg Min Pressure: 100 gm Sensing area: 1.4 cm (Dia.) Shape: Circular Length: 6 cm | FSR Sensor • Force Sensor • Pressure Sensor • Round Force Sensor • Force Sensitive Resistor |
| No Image | EDT-00006-B | Force Sensor - SQUARE | EM - Electronic-Electrical Modules | Interlink Electronics, SparkFun Electronics, DFRobot, Adafruit Industries, Ohmite | This is a force sensitive resistor with a square, 1.75 x 1.5", sensing area. This FSR will vary its resistance depending on how much pressure is being applied to the sensing area. The harder the force, the lower the resistance. When no pressure is being applied to the FSR its resistance will be larger than 1M?. This FSR can sense applied force anywhere in the range of 100g-10kg. Just Connect a resistor to form a voltage divider and measure the voltage at the junction to find the force applied. These sensors are simple to set up and great for sensing pressure, but they aren't incredibly accurate. This sensor can be easily interfaced with Microcontrollers, Arduino Boards, Raspberry Pi, etc. using an Analog to Digital Converter (ADC). | Actuation Force: 0.1 N Clock Speed: 16MHz | FSR Sensor • Pressure Sensor • Force Sensitive Resistor • Square Force Sensor • Touch Sensor |
| No Image | EMA-00002-A | SSD1306 0.96 inch I2C OLED display | EM - Electronic-Electrical Modules | Solomon Systech, SparkFun, DFRobot | The SSD1306 0.96 inch I2C OLED Display is a compact monochrome graphical display module commonly used with Arduino, ESP32, Raspberry Pi, and other microcontrollers. It typically features a 128x64 pixel resolution and uses the SSD1306 OLED driver IC with an I2C communication interface. | Product Type: OLED Display Module Display Size: 0.96 inch Driver IC: SSD1306 Resolution: 128 x 64 Pixels Operating Voltage: 3.3V – 5V DC | SSD1306 OLED Display • 0.96 OLED Module • I2C OLED Display • OLED Screen Module |
| No Image | EMA-00003-A | Programmable RGB 60 LED strip | EM - Electronic-Electrical Modules | Worldsemi, APA Electronics, Pololu | The Programmable RGB 60 LED Strip is an addressable LED strip containing 60 individually controllable RGB LEDs per meter, commonly based on WS2812B, WS2811, or SK6812 driver ICs. Each LED can display different colors and brightness levels independently, allowing dynamic lighting effects, animations, scrolling patterns, and smart visual displays. | Product Type: Programmable RGB LED Strip LED Type: WS2812B / WS2811 LEDs Per Meter: 60 LED Colors: RGB Full Color Operating Voltage: 5V DC (WS2812B) / 12V (WS2811) | Programmable RGB LED Strip • WS2812B LED Strip • NeoPixel LED Strip • Addressable RGB Strip |
| No Image | EMA-00006-A | Buzzer module | EM - Electronic-Electrical Modules | Generic, Keyes, Elegoo, SunFounder, DFRobot | This is Small PCB Mountable 5V . It is great to add Audio Alert to your electronic designs. It operates on 5V supply, uses a coil element to generate an audible tone. | Voltage Rating: 5VDC Operating Voltage (VDC): 5 Pin Spacing (mm): 6 Material: Plastic Color: Black Width (mm): 12 (Body Diameter) Height (mm): 8 Weight (g): 1 (approx) Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm | buzzer • buzzer module • sound • alarm • electronic • module • 5v |
| No Image | EMA-00006-B | Passive Buzzer Module | EM - Electronic-Electrical Modules | ED Series / Generic Compatible, KEYESTUDIO | Passive buzzer module designed to generate variable tones using PWM or frequency control. Operates from 1.5V to 15V DC and produces tones in the 1.5–2.5 kHz range. Ideal for alarms, alerts, Arduino projects, and microcontroller-based sound applications. | Model: Passive Buzzer Module Operating Voltage (VDC): 1.5 – 15 Max Operating Current (mA): 25 Tone Generator Frequency Range (kHz): 1.5 – 2.5 Mounting Type: PCB Mount Pin Pitch: 2.54 mm Compatibility: Arduino / Microcontrollers Length (mm): 15 Width (mm): 19.7 Height (mm): 10 Weight (g): 1 (approx.) Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H): 6 x 4 x 2 cm | Passive Buzzer • KY-006 Module • Arduino Buzzer • PWM Buzzer • Sound Module |
| No Image | EMC-00002-A | ESP8266 wifi module | EM - Electronic-Electrical Modules | Espressif Systems, AI-Thinker, SparkFun | The ESP8266 WiFi Module is a low-cost microcontroller with built-in WiFi capability used for IoT (Internet of Things) applications. It allows devices to connect to WiFi networks and communicate with servers, cloud platforms, or mobile apps. | Product Type: WiFi Microcontroller Module Core Chip: ESP8266EX CPU: 32-bit Tensilica L106 Operating Voltage: 3.3V | ESP8266 WiFi Module • ESP8266 NodeMCU • ESP8266 ESP-01 • WiFi IoT Module • Arduino WiFi Module • ESP8266 Wireless Module • ESP8266 ESP-12E • ESP8266 IoT Board |

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|----------|--------------------|------------------------------------------|------------------------------------|------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No Image | EMC-00006-A | GSM-GPRS Module (SIM800L) | EM - Electronic-Electrical Modules | SIMCom, DFRobot, Waveshare | SIM800L GSM/GPRS module is a miniature GSM modem, which can be integrated into a great number of IoT projects. You can use this module to accomplish almost anything a normal cell phone can: SMS text messages, make or receive phone calls, connecting to the internet through GPRS, TCP/IP, and more! To top it off, the module supports quad-band GSM/GPRS network, meaning it works pretty much anywhere in the world. An antenna is made of wire – very useful in narrow places. | IC Chip: SIM800L Input Voltage: 3.4V ~ 4.4V Peak Current: 2 A | SIM800L • GSM Module • GPRS Module • SMS Module • IoT Module • Arduino GSM • ESP8266 GSM |
| No Image | EMC-00006-B | GSM-GPRS Module (SIM900A) | EM - Electronic-Electrical Modules | SIMCom, DFRobot, Itead Studio | The onboard two set power supply interface VCC5 5V power supply, VCC4 interface, 3.5--4.5V power supply, optional power on self-starting (default), and control start. The onboard SMA (default) and IPXmini antenna interface, SIM900A interface reserved reset. The size of the module is 49*50, all the new and original device. The computer can give early computer debugging USB module power supply, a very large amount of data under the condition of the recommended current more than 1A. Standby dozens of MA data can be set to provide dormancy, dormancy of 10MA low power. Support 2, mobile phone 3.4G card. The serial port circuit: support for 3.3V single-chip microcomputer. TTL serial port support 3.3 and 5V single-chip microcomputer. The SIM card circuit to increase the SMF05C ESD chip. Antenna circuit: guarantee short and straight, so as to ensure the signal strength. PCB display screen printing mark: each interface, convenient development two times, the SIM900/A hardware completely follows the design when the design manual. | Frequency bands: Dual-band GPRS connectivity: GPRS multi-slot class 10 (default) , GPRS multi-slot class 8 (option) Operating Temperature Range: -30 to 80 °C Supply Voltage: 3.4 – 4.5 V Dimensions (LxWxH): 8.5x5.7x2cm (approx) | GSM Module • GPRS Module • SMS Module • IoT Module • Arduino GSM • SIM900A |
| No Image | EMS-00003-B | Accelerometer module GY-61 (ADXL335) | EM - Electronic-Electrical Modules | N/A | | | |
| No Image | EMS-00003-C | Accelerometer module MMA7361 | EM - Electronic-Electrical Modules | Freescalse Semiconductor, DFRobot, Elecrow | The MMA7361 Accelerometer Module is a low-power 3-axis analog accelerometer sensor designed to measure acceleration, tilt, vibration, orientation, and motion along X, Y, and Z axes. It is based on the Freescale/NXP MMA7361L MEMS accelerometer IC and provides analog voltage outputs proportional to acceleration values. | Product Type: 3-Axis Accelerometer Module Model: MMA7361L Sensor Type: MEMS Accelerometer Axes: X, Y, Z Operating Voltage: 3.3V – 5V DC | Tilt Sensor Module • MMA7361 Accelerometer • Triple Axis Accelerometer • 3-Axis Accelerometer Module |
| No Image | EMS-00004-C | MAX4466 Electret Microphone | EM - Electronic-Electrical Modules | Analog Devices / Maxim Integrated, SparkFun, DFRobot, Keyestudio | The MAX4466 Electret Microphone Module is a low-noise audio amplifier module designed for sound detection and audio signal monitoring applications. It uses an electret condenser microphone along with the MAX4466 operational amplifier IC to provide amplified analog audio output suitable for microcontrollers and embedded systems. | Product Type: Electret Microphone Module Main IC: MAX4466 Output Type: Analog Operating Voltage: 2.4V – 5.5V DC | MAX4466 Microphone Module • Electret Microphone Amplifier • Sound Sensor Module • Audio Detection Sensor |
| No Image | EMS-00006-A | PIR Motion Sensor | EM - Electronic-Electrical Modules | HC, DFRobot, SparkFun, Keyestudio | The PIR Motion Sensor is a passive infrared (PIR) detection module used to detect human movement and body heat based on infrared radiation changes. The most common version is the HC-SR501 PIR sensor module, which uses a pyroelectric infrared sensor and Fresnel lens to detect motion within its sensing range. (components101.com) | Product Type: PIR Motion Sensor Model: HC-SR501 Sensor Type: Passive Infrared Operating Voltage: 5V – 20V DC Detection Distance: 3 – 7 meters | Motion Detection Sensor • PIR Motion Sensor • HC-SR501 PIR Sensor • Human Motion Sensor |
| No Image | EMS-00010-H | Hydrogen Gas Sensor - MQ-8 - SEN-10916 | EM - Electronic-Electrical Modules | SparkFun Electronics, Hanwei Electronics, Winsen Electronics, SparkFun | The MQ-8 Hydrogen Gas Sensor is a semiconductor-based gas detection sensor designed to detect hydrogen (H ₂) gas concentration in air. It is highly sensitive to hydrogen and can detect gas concentrations ranging from 100 ppm to 10,000 ppm. The sensor uses a tin dioxide (SnO ₂) sensing layer whose resistance changes when exposed to hydrogen gas. The module provides both analog and digital outputs, making it easy to interface with Arduino, ESP32, Raspberry Pi, STM32, and other microcontrollers. | Product Type: Hydrogen Gas Sensor Model: MQ-8 SparkFun SKU: SEN-10916 Detectable Gas: Hydrogen (H ₂) Detection Range: 100 – 10,000 ppm Operating Voltage: 5V DC | MQ-8 Gas Sensor • Hydrogen Gas Sensor • H2 Gas Detector • MQ8 Sensor Module • Hydrogen Detection Sensor • Arduino Gas Sensor • ESP32 Hydrogen Sensor • Gas Leakage Sensor |
| No Image | EMS-00015-A | Touch keyboard TTP229 16 keys capacitive | EM - Electronic-Electrical Modules | Tontek Design Technology, Robocraze, Keyestudio | The TTP229 16-Key Capacitive Touch Keyboard is a touch-sensitive input module based on the TTP229 capacitive sensing IC. Unlike traditional membrane or mechanical keypads, this module detects finger touch using capacitive sensing technology, providing silent, durable, and highly responsive operation. | Product Type: Capacitive Touch Keypad IC Used: TTP229 Number of Keys: 16 Key Layout: 4x4 Operating Voltage: 2.4V – 5.5V DC | TTP229 Touch Keypad • 16-Key Capacitive Keyboard • 4x4 Touch Sensor Module • Arduino/ESP32 Touch Input Module |

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|----------|--------------------|---------------------------------------------------------|------------------------------------|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No Image | EMS-00016-A | Water Flow Sensor YF-G1 | EM - Electronic-Electrical Modules | YF Electronics, DFRobot, FlyRobo, Robocraze | The YF-G1 Water Flow Sensor is a hall-effect liquid flow meter designed for measuring the flow rate of water and other non-corrosive liquids in pipelines. It contains an internal rotor with a magnet that spins when liquid flows through the sensor. The built-in hall-effect sensor detects the magnetic rotation and generates pulse signals proportional to the flow rate. | Product Type: Water Flow Sensor Model: YF-G1 Sensor Type: Hall Effect Flow Meter Operating Voltage: 5V – 18V DC Working Current: ? 15 mA Flow Range: 1 – 30 L/min | Water Flow Sensor • Hall Effect Flow Sensor • Liquid Flow Meter • Flow Rate Sensor • YF-G1 Sensor • Industrial Water Flow Sensor • Arduino Flow Sensor • Pipe Flow Detection Module |
| No Image | EMS-00016-B | Water Flow Sensor YF-S401 | EM - Electronic-Electrical Modules | YF Electronics, DFRobot, FlyRobo, Robocraze | The YF-S401 Water Flow Sensor is a compact hall-effect liquid flow meter used to measure water flow rate in pipes and tubing systems. Inside the sensor, a rotor with magnets spins as water passes through it. The hall-effect sensor generates pulse signals proportional to the flow rate. It is widely used in water dispensers, smart irrigation systems, liquid monitoring systems, coffee machines, industrial automation, and Arduino/ESP32 projects. | Product Type: Water Flow Sensor Model: YF-S401 Sensor Type: Hall Effect Flow Meter Operating Voltage: 5V – 18V DC Working Current: ? 15 mA Flow Range: 0.3 – 6 L/min | YF-S401 Sensor • Water Flow Sensor • Hall Effect Flow Sensor • Liquid Flow Meter • Flow Rate Sensor • Arduino Water Flow Sensor • Flow Detection Module |
| No Image | EMS-00026-A | HMC5883L Triple Axis Compass Magnetometer Sensor Module | EM - Electronic-Electrical Modules | Honeywell, ITEAD Studio, DFRobot, Adafruit, SparkFun | HMC5883L Triple Axis Compass Magnetometer Sensor Module is a 3-axis digital compass sensor used for navigation, heading detection, robotics, drones, GPS systems, and Arduino projects. The module communicates through the I2C interface and measures magnetic field strength across X, Y, and Z axes for accurate compass heading and orientation detection. | Product Type: Triple Axis Magnetometer Sensor Model: HMC5883L Number of Axes: 3 Axis Communication Interface: I2C Operating Voltage: 3.3V – 5V ADC Resolution: 12-bit | HMC5883L Sensor • Magnetometer Module • Compass Sensor • Triple Axis Compass • GY-271 Sensor • GY-273 Module • Arduino Compass Sensor |

| Image | Part Number | Name | Category | Manufacturer | Description | Specification | Tags |
|----------|--------------------|------------------------------------------------------------------------|------------------------|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| No Image | MMC-00006-A | DC Jack | MM - Mechanical Module | CUI Devices, Kyton, SparkFun, Adafruit | 9V DC jack connector designed for power supply connections in electronic circuits, Arduino systems, embedded devices, robotics, and DIY electronics projects. It provides secure and stable DC power connectivity for adapters, batteries, and external power sources in low-voltage electronic applications. | Connector Type: DC Barrel Jack Input Voltage: 9V DC Connector Size: 5.5mm x 2.1mm | DC jack • 9V connector • barrel jack • power connector • DC socket • Arduino power jack |
| No Image | MMD-00002-D | Digital Servo Motor 360 Degree | MM - Mechanical Module | TowerPro, Probots, DFRobot, Adafruit, SparkFun | MG996R Digital Servo Motor 360 Degree is a high-torque continuous rotation servo motor widely used in robotics, robotic arms, RC vehicles, automation systems, pan-tilt mechanisms, and Arduino projects. It features metal gears, PWM control, and continuous 360° rotation capability. | Product Type: Digital Servo Motor Model: MG996R Rotation Type: 360° Continuous Rotation Operating Voltage: 4.8V – 7.2V DC Rated Voltage: 6V DC Stall Torque: 10kg-cm – 13kg-cm | Arduino Servo • MG996R Servo • 360 Degree Servo • Digital Servo Motor • Metal Gear Servo • High Torque Servo • Robotics Servo |
| No Image | MMD-00006-A | Small Reduction Stepper Motor - 5VDC 32-Step 1/16 Gearing | MM - Mechanical Module | Adafruit, Songle Motor, Generic Stepper Motors, SunFounder | The Small Reduction Stepper Motor – 5VDC 32-Step 1/16 Gearing is commonly known as the 28BYJ-48 stepper motor. It is a compact geared unipolar stepper motor widely used in Arduino projects, robotics, automation systems, camera sliders, smart locks, and educational electronics. The internal reduction gearbox provides higher torque and precise low-speed rotation. | Product Type: Geared Stepper Motor Model: 28BYJ-48 Operating Voltage: 5V DC Gear Reduction Ratio: 1/64 Steps Per Revolution: 2048 Steps | Arduino Motor • 5V Stepper Motor • Reduction Stepper Motor • 28BYJ-48 • Geared Stepper Motor • Mini Stepper Motor • DIY Robotics Motor |
| No Image | MMM-00006-A | Castor wheel | MM - Mechanical Module | Blickle, TENTE, Shepherd Hardware, Caster Concepts | 1-inch castor wheels are compact rolling wheels used for robotics, small trolleys, DIY platforms, movable enclosures, furniture, carts, and electronic project bases. These wheels are available in swivel and fixed types with plastic, rubber, or nylon wheel materials. | Product Type: Castor Wheel Wheel Size: 1 inch Load Capacity: 5kg – 20kg Rotation: 360° Swivel | DIY Hardware • Castor Wheel • 1 Inch Wheel • Mini Castor • Swivel Wheel • Furniture Wheel • Robot Wheel |
| No Image | TLC-00006-A | Brass Wool Solder Tip | TL - Tools | Pro'sKit, Hakko, YIHUA, Bakon | Brass wool solder tip cleaners are used to clean soldering iron tips without reducing tip temperature. Made from brass shavings or brass wool, they effectively remove oxidation, burnt flux, and solder residue while extending soldering tip life. Commonly used in electronics repair, PCB soldering, and DIY workshops. | Product Type: Brass Wool Tip Cleaner Usage: Soldering Tip Cleaning Compatible With: Soldering Stations & Irons | Brass Wool Cleaner • Solder Tip Cleaner • Soldering Cleaner • Brass Sponge • Tip Cleaning Ball • Soldering Accessory |
| No Image | TLK-00002-A | Hot Pro'sKit 8PK-2061 6PCS Precision Screwdriver Set Cross Screwdriver | TL - Tools | Pro'sKit, Jakemy, Stanley, Bosch | Pro'sKit 8PK-2061 is a 6-piece precision screwdriver set designed for electronics repair, PCB work, mobile repair, watches, laptops, and precision DIY applications. It includes cross and slotted precision screwdrivers with ergonomic anti-slip handles and hardened steel tips. | Product Type: Precision Screwdriver Set Number of Pieces: 6 pcs Screwdriver Type: Cross & Slotted Usage: Mobile, Laptop, DIY Repair | DIY Tool • Electronics Repair Tool • Precision Screwdriver Set • Cross Screwdriver • Phillips Screwdriver • Mini Screwdriver Set |
| No Image | TLK-00003-A | Screwdriver Set 6pcs | TL - Tools | Stanley, STANLEY Tools, Stanley Black & Decker | Stanley 92-002-2 Cushion Grip is a 6-piece screwdriver set designed for electronics repair, household maintenance, workshop applications, and DIY use. It features ergonomic cushion grip handles, chrome vanadium steel shafts, and durable precision tips for better torque and comfort. | Product Type: Cushion Grip Screwdriver Set Number of Pieces: 6 pcs Tip Types: Phillips & Slotted Usage: Tightening & Loosening Screws | DIY Tool • Cushion Grip Screwdriver • Stanley Screwdriver Set • 6pcs Screwdriver Kit • Hand Tool Kit • Repair Tool |