

Parts Export

Generated: 2026-04-19 17:24:16

Total Parts: 8









Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COC-00008-A	Desoldering Wick (2.5mm Copper Solder Braid)	CO - Consumables	Noel Solder Wire, Hakko, Velleman, Pro'sKit	Solder wick is composed of fine copper threads braided together. Flux is added to help molten solder flow from unwanted areas (such as PCB pads or jumpers) into the wick. It is commonly used for removing excess solder during PCB repair, rework, and component replacement. Solder wick is also known as desolder braid. This version offers good performance at an affordable price. It efficiently absorbs solder and is suitable for DIY users, repair technicians, and lab use.	Material: Copper (Braided with Flux Coating) Width: 2.5 mm Usage: PCB Desoldering / Rework Shipping Weight: 0.008 kg Shipping Dimensions: 8 x 5 x 2 cm	Desoldering Wick • Solder Braid • 2.5mm • Copper • Flux Coated • PCB Rework • DIY • Repair • Lab Use
	EDD-00002-B	Green LED (8mm, DIP Type)	ED - Electronic Device	Generic	Green Light Emitting Diode (LED) used as an indicator in electronic circuits. Emits bright green light with a transparent lens, ideal for TVs, monitors, telephones, and project indicators. Suitable for general indicator applications, prototyping, and educational electronics projects.	Case/Package: DIP Diameter (mm): 8 Mounting Type: Through Hole Lens Appearance: Transparent Color: Green Forward Voltage (V): 3.5 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Indicator LED • Through Hole LED • DIP LED • Green LED • 8mm LED
	EDR-00001-680Z	0.25W Resistor - 680 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 680 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 680 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	resistor • carbon film • 0.25w • passive • axial • 680ohm
	EMA-00003-B	WS2812B 8-Bit RGB NeoPixel LED Module (8x 5050 LEDs)	EM - Electronic-Electrical Modules	Worldsemi Co., Ltd., Generic / OEM	The WS2812B 8-Bit RGB LED Module features 8 individually addressable 5050 RGB LEDs with integrated driver ICs. It operates on 5V and uses a single-wire communication protocol for precise color and brightness control. Ideal for programmable lighting, animations, IoT devices, and Arduino-based creative projects.	LED Model: WS2812B Package Type: 5050 SMD Number of LEDs: 8 Color Type: Full-Color RGB Bit Depth: 8-bit per channel (24-bit RGB total) Operating Voltage: DC 5V Control Interface: Single Data Line (Serial) Communication Protocol: One-Wire Timing Protocol PCB Color: White Mounting Type: Solderless / Plug-and-Play Length (mm): 105 Width (mm): 10 Height (mm): 6 Weight (g): 8 Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H cm): 12 x 8 x 1	Arduino Compatible • WS2812B • NeoPixel Module • 8 LED RGB • 5050 SMD • Addressable LED • 5V RGB Strip • Programmable LED
	EMA-00008-A	Single Channel Relay Module (12V, High/Low Level Trigger)	EM - Electronic-Electrical Modules	Single Relay, Generic / OEM	The Single Channel 12V Relay Module allows low-voltage microcontrollers to safely control high-voltage AC or DC loads. It supports both high-level and low-level trigger modes and includes status LEDs for operation indication. Ideal for home automation, motor control, IoT systems, and industrial switching applications.	Model: Relay Module Number of Channels: 1 Operating Voltage (VDC): 12 Trigger Type: High-Level / Low-Level Trigger Relay Contact Rating (AC): 10A @ 250V AC Relay Contact Rating (AC Alternate): 15A @ 125V AC Contact Type: COM, NO (Normally Open), NC (Normally Closed) Interface: 2.54 mm Header Pins Output Connection: 3-Pin Screw Terminal Indicators: Power LED + Relay Status LED Length (mm): 50 Width (mm): 25 Height (mm): 20 Weight (g): 16 Shipping Weight: 0.025 kg Shipping Dimensions (L x W x H cm): 7 x 4 x 3	Arduino Compatible • 12V Relay Module • Single Channel Relay • High/Low Trigger • Single SRD-12VDC-SL-C • SPDT Relay • 10A 250VAC • IoT Switching Module
	EMA-00008-B	2 Channel Relay module	EM - Electronic-Electrical Modules	Single, Keyes, SunFounder, Elegoo, Generic	This is a 5V 2 Channel Relay Module, be able to control various appliances, and other equipment with large current. It can be controlled directly by Microcontroller (8051, AVR, PIC, DSP, ARM, ARM, MSP430, TTL logic).5V 2-Channel Relay interface board and each one needs 15-20mA Driver Current Equipped with high-current relay, AC250V 10A; DC30V 10A Standard interface that can be controlled directly by microcontroller (8051, AVR, PIC, DSP, ARM, ARM, MSP430, TTL logic) Indication LED's for Relay output status.	No. of Channels: 2 Operating Temperature Range: -40 to 85 °C Operating Voltage: 2.5 ~ 5.5 V (DC) Switching Voltage(AC): 240V@10A Switching Voltage(DC): 30V@10A Trigger Current: 20 mA Trigger Voltage: 5V (DC) Length: 4.3 cm Height: 1.7 cm Width: 4.3 cm	arduino • module • 5v • relay module • 2 channel • switching • control

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EMA-00009-A	ISD1820 Voice Recording & Playback Module with Mic and Speaker	EM - Electronic-Electrical Modules	Nuvoton Technology Corporation, Generic / OEM	ISD1820 Module, Voice Recorder, 10s Audio, Playback Module, Onboard Mic, 8Ω Speaker, Arduino Compatible, Sound Board . The ISD1820 Voice Recording Module allows up to 10 seconds of audio recording stored in non-volatile analog flash memory. It features an onboard electret microphone, push-button controls, and supports external triggering via microcontroller.	IC Chip: ISD1820 Operating Voltage (VDC): 3 – 5 Recording Duration: Up to 10 seconds Memory Type: Non-Volatile Analog Flash Microphone: Onboard Electret Microphone Speaker: 8 Ω, 0.5W Speaker Cable Length (cm): 20 Speaker Diameter (mm): 40 Control Options: Push Buttons or Microcontroller Digital Pin Interface: 2.54 mm Header Pins Length (mm): 42 Width (mm): 33.5 Height (mm): 11.5 Weight (g): 20 Shipping Weight: 0.022 kg Shipping Dimensions (L x W x H cm): 8 x 6 x 3	Arduino Compatible • ISD1820 Module • Voice Recorder • 10s Audio • Playback Module • Onboard Mic • 8Ω Speaker • Sound Board
	EQE-00002-A	Digital Multimeter (DT830D Type, Yellow)	EQ - Equipment/Instrument	Generic / OEM, YX-360, Mastech, Victor, Pro'sKit	This compact digital multimeter is designed for day-to-day electrical testing needs. It is suitable for basic continuity checks, voltage measurements, and current testing. A multimeter (Volt-Ohm Meter or VOM) is a multifunction measuring instrument that combines voltage, current, and resistance measurement in one unit. Digital multimeters (DMM) display measured values numerically on an LCD screen. This device supports testing of AC/DC voltage, DC current, resistance, diode, buzzer continuity, transistor hFE, battery testing, and square wave output. Ideal for students, DIY users, lab use, and technicians.	Item Type: Multimeter Model Type: Digital Multimeter (DT830D Type) Probe Length: 60 cm Length: 120 mm Width: 70 mm Height: 27 mm Weight: 160 g Shipping Weight: 0.18 kg Shipping Dimensions: 15 x 8 x 3.5 cm	DT830D • Digital Multimeter • AC/DC Tester • LCD Display • VOM