

# Parts Export

Generated: 2026-04-19 17:18:42

Total Parts: 16







Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	<b>COC-00003-B</b>	Hot Melt Glue Sticks (11mm, 5pcs Pack)	CO - Consumables	Generic / OEM, 3M, Pro'sKit, Stanley, Bosch	All-purpose hot melt glue sticks suitable for bonding applications in DIY, electronics, crafts, packaging, and general repairs. Designed for use with standard temperature glue guns operating around 200°C and compatible with 11mm diameter glue stick slots. Provides strong adhesion on plastic, wood, fabric, paper, and light materials.	Item Type: Hot Melt Glue Sticks Stick Diameter: 11 mm Pack Quantity: 5 Pieces Shipping Weight: 0.2 kg Shipping Dimensions: 4 x 4 x 4 cm	Glue Sticks • 11mm Glue Stick • Hot Melt Adhesive • Glue Gun Refill • DIY Adhesive
	<b>COE-00001-C</b>	CR2025 3V Lithium Coin Cell	CO - Consumables	Panasonic	.Panasonic CR2025 is a 3V lithium coin cell battery designed for long-lasting and reliable power in compact electronic devices. Built using Lithium Manganese Dioxide (LiMnO <sub>2</sub> ) chemistry, it offers stable discharge characteristics and a shelf life of up to 10 years under proper storage conditions. Suitable for car key remotes, medical devices, digital watches, calculators, fitness devices, memory backup systems, and other small electronics.	Battery Type: Lithium Coin Cell Battery Size: CR2025 Chemistry: Lithium Manganese Dioxide (LiMnO <sub>2</sub> ) Nominal Voltage: 3 V Nominal Capacity: 165 mAh Diameter: 20 mm Height: 2.5 mm Termination Style: Pressure Contacts Operating Temperature: -30°C to +60°C Weight (Unit): 2.3 g Shipping Weight: 0.008 kg Shipping Dimensions: 9.2 x 7.5 x 1 cm	CR2025 Battery • 3V Coin Cell • Lithium Battery • Panasonic Battery • Button Cell
	<b>COE-00002-A</b>	Plusivo 30AWG Silicone Hookup Wire Kit	CO - Consumables	Plusivo	Assorted 30AWG silicone hookup wires, ultra-flexible and durable for electronics and DIY projects. Includes 6 colors &times; 20m each, totaling 120 meters, perfect for prototyping and wiring. Bonus items like heat shrink tubes, mini wire stripper, and colored wire ties included in a dispensing box.	Brand: Plusivo Item Type: Hookup Wire Kit Wire Gauge: 30 AWG Conductor Material: 0.08 mm Tinned Copper (Stranded) Insulation Material: Silicone Rated Voltage: 300 V Rated Temperature: 200°C Wire Length: 20 meters per color (6 colors) Total Wire Length: 120 meters Weight: 285 g Shipping Weight: 0.27 kg Shipping Dimensions (L x W x H): 15 x 7 x 7 cm	Hookup Wire • Silicone Wire • Stranded Wire • 30AWG • Prototyping • Electronics
	<b>EDD-00002-D</b>	Blue LED (3mm, Round, DIP Type)	ED - Electronic Device	Generic	Blue Light Emitting Diode (LED) used as an indicator in electronic circuits. Emits bright blue light with a round transparent body, ideal for TVs, monitors, telephones, and computers. Suitable for educational, DIY, prototyping, and professional electronics applications.	Mounting Type: Through Hole Through Hole LED Size (mm): 3 No. of Pins: 2 Color: Blue Head Shape: Round Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Indicator LED • Through Hole LED • 3mm LED • DIP LED • Blue LED • Round LED
	<b>EDD-00002-E</b>	White LED (3mm, DIP Type)	ED - Electronic Device	ED Series / Generic	White Light Emitting Diode (LED) used as an indicator or illumination source in electronic circuits. Emits bright white light from a transparent housing, ideal for display panels, devices, and project indicators. Suitable for hobby, prototyping, and professional electronics applications.	Manufacturer: ED Series / Generic Compatible – White LED (3mm, DIP Type) Case/Package: DIP Mounting Type: Through Hole Lens Appearance: Transparent Color: White Forward Voltage (V): 2.8 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Weight: 1 x 1 x 1 cm	Indicator LED • Through Hole LED • White LED • 3mm LED • DIP LED
	<b>EDD-00003-A</b>	RGB Multi-Color LED Module (Common Cathode, 5mm)	ED - Electronic Device	ED Series / XINGLIGHT, XINGLIGHT	5mm common cathode RGB LED with transparent lens for multi-color indication. Combines red and green-yellow emission in a single through-hole package. Ideal for indicator panels, DIY electronics, and visual feedback systems.	Manufacturer: XINGLIGHT Model No.: XL-A524SURSYGC Package: Plugin, D = 5mm Forward Current (mA): 20 Color Temperature: - Peak Wavelength (nm): 640 (Red) 572 (Green: Yellow) Luminous Intensity (mcd): 600 (Red) 550 (Green: Yellow) Lens Color: Colorless Transparent Diode Configuration: Common Cathode Wavelength – Dominant (nm): 635–640 (Red) 565–575 (Green: Yellow) Operating Temperature (°C): -20 ~ +85 Illumination Color: Red, Green-Yellow Viewing Angle: 30° Lamp Holder Type: 5mm Round Head Power (mW): 50 Forward Voltage (Vf): 2.3V (Red) 2.4V (Green: Yellow) Mounting Type: Through Hole Compliance: RoHS	RGB LED • 5mm LED • Common Cathode LED • Indicator LED • Through Hole LED











Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	<b>EDD-00003-B</b>	RGB Multi-Color LED Module (Common Anode, 5mm)	ED - Electronic Device	Jameco ValuePro, Jameco ValuePro, Adafruit Industries	5mm high-brightness RGB LED with common anode configuration. Emits red, green, and blue light for color mixing and display applications. Ideal for indicators, Arduino projects, decorative lighting, and DIY electronics.	Manufacturer: Generic Model Type: Common Anode RGB LED Package: 5mm Round (Clear Lens) Color: Red, Green, Blue Configuration: Common Anode Brightness: High Current Consumption: Low Operating Voltage: 2.0–3.2V (per color) Forward Current (mA): 20 (per channel) Power Efficiency: High Luminous Output, Low Heat Material: Epoxy Resin, Gold Wire Leads Mounting Type: Through Hole Item Size: 5mm Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	RGB LED • 5mm LED • Indicator LED • Through Hole LED • Common Anode LED
	<b>EDK-00004-A</b>	Metal Film Resistor Assorted Kit (600 pcs, 30 Values)	ED - Electronic Device	Generic	Assorted kit of 600 metal film resistors with 30 different values, 20 pcs each. 1/4W, 1% tolerance resistors suitable for precise electronic, DIY, and educational projects.	Manufacturer: Generic Model Name: 600 pcs. Metal Film Resistor Assorted kit – 30 Kinds Power Rating: 1/4W Tolerance (%): 1 Material Type: Metal Film Package Type: Axial Lead Temperature Stability: High (Better than Carbon Film) Noise Level: Low Frequency Suitability: Suitable for RF and High-Frequency Applications Number of Values: 30 Total Quantity: 600 pcs Quantity per Value: 20 pcs Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Ideal for prototyping • learning resistor color codes • testing • and circuit experiments.
	<b>EDM-00001-A</b>	Tactile Push Button Switch Round Key (12x12x7.3mm, 25PCS Kit)	ED - Electronic Device	OMRON, E-Switch	12x12x7.3mm tactile push button switches with momentary ON-OFF operation. Rated for 12V DC and 120mA with responsive tactile feedback. Includes 25 color-coded round keycaps and storage box for prototyping and DIY projects.	Item Type: Micro Switch Model: Tactile Push Button Switch Operation Mode: ON-OFF Contact Type: Momentary Current Rating: 120mA Operating Voltage: 12V DC Switch Type: Push Button Material: Metal and Plastic Mounting Type: Surface Mount Button Size (mm): 12x12x7.3 Operating Temperature (°C): -25 to +70 Lifespan: ~1000 Cycles Box Dimensions (mm): 127.1 x 68.3 x 21.9 Weight (g): 55 Shipping Weight: 0.06 kg Shipping Dimensions (L x W x H): 13 x 7 x 3 cm	Tactile Switch • Push Button • 12x12mm Switch • Momentary Switch • Arduino Button Kit
	<b>EDR-00001-330Z</b>	0.25W Resistor - 330 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 330 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 330 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	
	<b>EDR-00002-10K0</b>	10K? Potentiometer (3-Pin, 15mm Shaft)	ED - Electronic Device	ED Series / Generic Compatible, Bourns, Alpha, Omega	10KΩ; rotary potentiometer used for adjusting voltage, current, and signal levels in electronic circuits. Features smooth single-turn rotation with a durable 15mm shaft and through-hole mounting. Ideal for audio control, Arduino analog input, sensor calibration, and embedded system tuning.	Manufacturer: Generic Resistance (Ohm): 10K Tolerance (%): 20 Temperature Coefficient: ±100ppm/°C Operating Temperature (°C): -40 to 80 Mounting Type: Through Hole Shaft Type: 15mm Rotary Shaft Adjustment Type: Single Turn Length (mm): 20 Width (mm): 17 (Body Diameter) Height (mm): 24 Weight (g): 6 Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	10K Potentiometer • Rotary Pot • Variable Resistor • WH148 Potentiometer • 3-Pin Pot
	<b>EMA-00003-B</b>	WS2812B 8-Bit RGB NeoPixel LED Module (8x 5050 LEDs)	EM - Electronic-Electrical Modules	Worldsemi Co., Ltd., Generic / OEM	The WS2812B 8-Bit RGB LED Module features 8 individually addressable 5050 RGB LEDs with integrated driver ICs. It operates on 5V and uses a single-wire communication protocol for precise color and brightness control. Ideal for programmable lighting, animations, IoT devices, and Arduino-based creative projects.	LED Model: WS2812B Package Type: 5050 SMD Number of LEDs: 8 Color Type: Full-Color RGB Bit Depth: 8-bit per channel (24-bit RGB total) Operating Voltage: DC 5V Control Interface: Single Data Line (Serial) Communication Protocol: One-Wire Timing Protocol PCB Color: White Mounting Type: Solderless / Plug-and-Play Length (mm): 105 Width (mm): 10 Height (mm): 6 Weight (g): 8 Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H cm): 12 x 8 x 1	Arduino Compatible • WS2812B • NeoPixel Module • 8 LED RGB • 5050 SMD • Addressable LED • 5V RGB Strip • Programmable LED
	<b>EMS-00013-A</b>	Infrared Obstacle Avoidance IR Sensor Module	EM - Electronic-Electrical Modules	Generic OEM Manufacturer, Keyestudio, HiLetgo, Elegoo, SunFounder	The Infrared Obstacle Avoidance Sensor Module detects nearby objects using reflected infrared light. It uses an IR transmitter&dash;receiver pair with an LM393 comparator to provide a digital active LOW output when an obstacle is detected. Ideal for robotics, smart cars, automation systems, and Arduino-based proximity detection projects.	Sensor Type: Infrared Reflective Obstacle Sensor Operating Voltage: 3.6V - 5V DC Output Type: Digital (Active Low) Main IC: LM393 Comparator Average Current Consumption: 0.06 mA Detection Angle: 35° Detection Distance: 2 cm – 30 cm (adjustable) Interface Pins: VCC, GND, OUT Indicator LED: Yes (Obstacle Detection Indicator) Sensitivity Adjustment: Onboard Potentiometer Dimensions (mm): 48 x 14 x 8 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (cm): 5 x 4 x 1	IR Obstacle Sensor • Infrared Reflective Module • LM393 Comparator • Active Low Output • Proximity Sensor • Arduino Compatible • Robot Sensor

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	<b>EQE-00002-A</b>	Digital Multimeter (DT830D Type, Yellow)	EQ - Equipment/Instrument	Generic / OEM, YX-360, Mastech, Victor, Pro'sKit	This compact digital multimeter is designed for day-to-day electrical testing needs. It is suitable for basic continuity checks, voltage measurements, and current testing. A multimeter (Volt-Ohm Meter or VOM) is a multifunction measuring instrument that combines voltage, current, and resistance measurement in one unit. Digital multimeters (DMM) display measured values numerically on an LCD screen. This device supports testing of AC/DC voltage, DC current, resistance, diode, buzzer continuity, transistor hFE, battery testing, and square wave output. Ideal for students, DIY users, lab use, and technicians.	Item Type: Multimeter Model Type: Digital Multimeter (DT830D Type) Probe Length: 60 cm Length: 120 mm Width: 70 mm Height: 27 mm Weight: 160 g Shipping Weight: 0.18 kg Shipping Dimensions: 15 x 8 x 3.5 cm	DT830D • Digital Multimeter • AC/DC Tester • LCD Display • VOM
	<b>TLP-00002-A</b>	Soldering Iron Kit – 3-in-1 (25W)	TL - Tools	TLP Series / Generic Compatible, Noel, Pro'sKit, Velleman	Be it beginner, hobbyist, or professional, soldering iron kits are essential tools for building circuit boards, repairing electronics, jewelry making, welding, and other precision tasks. This kit combines the basic tools used in general-purpose soldering work and includes necessary components required for soldering at your work desk. Best suited for DIY beginners, college project teams, and professional electronics hobbyists.	Item Type: Kit Soldering Iron Power: 25 Watt Suitable For: Beginner to Professional Shipping Weight: 0.4 kg Shipping Dimensions: 20 x 7 x 6 cm	Soldering Kit • 25W Soldering Iron • 3-in-1 Kit • DIY Soldering Set • Electronics Repair Kit
	<b>TLP-00003-A</b>	Soldering Iron Stand (25W Compatible)	TL - Tools	Generic / OEM, Pro'sKit, Velleman, Goot, Noel	The soldering iron stand 25W is a standardized support tool designed for safely holding soldering irons during operation. It is compatible with 25W or lower wattage soldering irons. The stand features a heavy-duty metal base for stability and a nickel-plated spring holder that securely holds the soldering iron while not in use. Ideal for electronics workbenches, college labs, DIY projects, and professional repair environments.	Suitable Wattage: 25 Watt (Max) Material: Metal Base with Steel Spring Holder Shipping Weight: 0.3 kg Shipping Dimensions: 20 x 6 x 3 cm	Soldering Stand • 25W • Iron Holder • Metal Base • Spring Holder