



# Parts Export

Generated: 2026-04-19 21:49:09

Total Parts: 2

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	<b>EDD-00003-B</b>	RGB Multi-Color LED Module (Common Anode, 5mm)	ED - Electronic Device	Jameco ValuePro, Jameco ValuePro, Adafruit Industries	5mm high-brightness RGB LED with common anode configuration. Emits red, green, and blue light for color mixing and display applications. Ideal for indicators, Arduino projects, decorative lighting, and DIY electronics.	Manufacturer: Generic Model Type: Common Anode RGB LED Package: 5mm Round (Clear Lens) Color: Red, Green, Blue Configuration: Common Anode Brightness: High Current Consumption: Low Operating Voltage: 2.0–3.2V (per color) Forward Current (mA): 20 (per channel) Power Efficiency: High Luminous Output, Low Heat Material: Epoxy Resin, Gold Wire Leads Mounting Type: Through Hole Item Size: 5mm Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	RGB LED • 5mm LED • Indicator LED • Through Hole LED • Common Anode LED
	<b>EMX-00001-A</b>	Arduino Uno	EM - Electronic-Electrical Modules	Arduino, Elegoo, HiLetgo, Keyestudio	The Arduino Uno R3 is a microcontroller development board based on the ATmega328P, designed for building interactive electronic projects. It features 14 digital I/O pins, 6 analog inputs, a 16 MHz clock, USB connectivity, and operates at 5 V. Compatible with the Arduino IDE and a wide range of shields, it is widely used in education, prototyping, and embedded system development.	Board Type: Uno With Cable: Yes Operating Voltage: 5 V Input Voltage Range: 6 – 20 V Analog I/O Pins: 6 Digital I/O Pins: 14 (6 x PWM) DC Current per I/O Pin: 40 mA Clock Speed: 16 MHz SRAM: 2 KB EEPROM: 1 KB Flash Memory: 32 KB Dimensions (L x W x H): 75 x 54 x 12 mm Weight: 28 g (without cable), 54 g (with cable)	ATmega328P • 5 V Board • 16 MHz Crystal • USB Interface • Microcontroller • Educational Kit • Open-Source Hardware • Breadboard Compatible