

Parts Export

Generated: 2026-07-25 08:46:55

Total Parts: 94

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COC-00003-A	Hot Glue Sticks 7 mm	CO - Consumables	Stanley, Surebonder	The Thermoplastic Adhesive Glue Sticks are used with hot glue guns for crafting, DIY projects, electronics assembly, and repairs. They melt quickly to form a strong bond on materials like plastic, wood, paper, and fabric. They are commonly used in workshops, prototyping, and educational projects for fast and durable adhesion.	Glue Stick Diameter: 7mm Melting Temperature: 120°C – 180°C Compatibility: 7mm Mini Glue Guns Stick Length: 100mm – 300mm	Hot Melt Adhesive • hot glue stick • glue gun stick • adhesive stick • 7mm glue stick • craft glue
No Image	COC-00001-A	Filament Tape	CO - Consumables	Dowell, 3M, Advance Tapes, Deta Electrical	The Insulation Filament Tape (25mm x 50m) is a high-strength adhesive tape reinforced with fiberglass for excellent tensile strength and tear resistance. It is used for bundling, sealing, reinforcing, and securing loads. It offers strong adhesion, heat resistance, and insulation properties, making it suitable for electrical, industrial, and DIY applications.	Operating Temperature: -18°C to +105°C Voltage Rating: Up to 600V Thickness: 0.178mm Flame Retardant: Yes	PVC Tape • Electrical Tape • Binding Tape • Insulation Tape • Cable Tape • Wire Management • Electronics Tape
No Image	COC-00001-B	Foam Tape	CO - Consumables	3M, Tesa, Nitto Denko, Avery Dennison, Hi-Bond	The Foam Tape Roll (50mm x 6mm) is a durable adhesive foam tape used for sealing, mounting, insulation, and vibration damping. It provides strong adhesion with cushioning that absorbs shocks and reduces noise. It is widely used in DIY projects, automotive work, electronics mounting, and professional installations.	Color: Black Thickness: 6mm Material: EVA Foam Length: 5 Meter Width: 50mm	Foam Tape • Double Sided Tape • EVA Foam Tape • PE Foam Tape • Acrylic Foam Tape
No Image	COC-00001-C	Masking Tape Roll	CO - Consumables	Avery Dennison, Advance Tapes, Shurtape, Intertape Polymer Group	The Masking Tape Roll (20mm x 20m) is a versatile adhesive tape used for painting, crafting, labeling, and general-purpose applications. It provides clean masking and removes easily without residue. It adheres well to surfaces like wood, metal, and glass and is widely used in DIY, workshop, and professional projects.	Tape Type: Pressure Sensitive Masking Tape Material: Crepe Paper Width: 12mm – 48mm Length: 10m – 50m Temperature Resistance: Up to 80°C	Electronics Tape • Masking Tape • Paper Tape • Crepe Tape • Painting Tape • PCB Masking
	COC-00006-A	Sandpaper Sheet	CO - Consumables	3M, Norton Abrasives	The Abrasive Sandpaper Sheet is used for smoothing, polishing, finishing, and surface preparation. It works on wood, metal, plastic, and other materials. It is commonly used in DIY projects, fabrication, electronics enclosures, and industrial finishing.	Product Type: Abrasive Sandpaper Sheet Abrasive Material: Aluminum Oxide / Silicon Carbide Grit Range: 60 – 3000 Grit Sheet Size: Standard 9x11 Inch	sandpaper • abrasive paper • sanding sheet • polishing paper • surface finishing
	COC-00007-A	Soldering Flux	CO - Consumables	Generic / OEM, Noel, Welfix, Mechanic, Pro'sKit	Soldering Flux Paste is used to improve solder flow and create strong, clean solder joints. It reduces oxidation and helps solder stick properly. It is commonly used in PCB work, wire connections, and electronics repair.	Item Type: Soldering Flux Paste Net Weight: 10 g Color: White / Yellow (as per brand batch) Usage: PCB, Wires, Electrical Components Packaging Type: Small Plastic Container	Flux Paste • 10g • Soldering Flux • PCB Repair • Low Smoke

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COE-00001-C	Panasonic Battery	CO - Consumables	Panasonic	The Panasonic CR2025 is a 3V lithium coin cell battery designed for compact electronic devices. It offers long-lasting, stable power and is commonly used in key remotes, watches, calculators, medical devices, and small electronics.	Battery Type: Lithium Coin Cell Battery Size: CR2025 Chemistry: Lithium Manganese Dioxide (LiMnO ₂) Nominal Voltage: 3 V Nominal Capacity: 165 mAh Diameter: 20 mm Height: 2.5 mm Termination Style: Pressure Contacts Operating Temperature: -30°C to +60°C Weight (Unit): 2.3 g Shipping Weight: 0.008 kg Shipping Dimensions: 9.2 × 7.5 × 1 cm	CR2025 Battery • 3V Coin Cell • Lithium Battery • Panasonic Battery • Button Cell
	COE-00002-A	Hookup Wire Kit	CO - Consumables	Plusivo	The Assorted 30AWG Silicone Hookup Wire Kit is a flexible wiring set for electronics and prototyping. It includes multiple colored wires, heat shrink tubes, and accessories for easy circuit building. It is widely used in Arduino projects, robotics, and embedded system wiring.	Brand: Plusivo Item Type: Hookup Wire Kit Wire Gauge: 30 AWG Conductor Material: 0.08 mm Tinned Copper (Stranded) Insulation Material: Silicone Rated Voltage: 300 V Rated Temperature: 200°C Wire Length: 20 meters per color (6 colors) Total Wire Length: 120 meters Weight: 285 g Shipping Weight: 0.27 kg Shipping Dimensions (L × W × H): 15 × 7 × 7 cm	Hookup Wire • Silicone Wire • Stranded Wire • 30AWG • Prototyping • Electronics
	COM-00001-A	3D Filament	CO - Consumables	Creality, eSUN, Hatchbox	High-quality 1.75mm white 3D printing filament designed for FDM/FFF 3D printers used in prototyping, educational models, robotics, product design, and engineering applications. It provides smooth extrusion, reliable layer adhesion, low warping, and consistent print quality for detailed prints and structural models.	Filament Type: PLA / ABS / PETG Filament Diameter: 1.75mm Color: White Spool Weight: 1kg Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • white filament • 1.75mm filament • FDM filament • 3D printer material
	COM-00001-B	3D Filament	CO - Consumables	Creality, eSUN, Hatchbox	High-quality 1.75mm black 3D printing filament designed for FDM/FFF 3D printers used in prototyping, robotics, engineering models, product design, and fabrication applications. It provides smooth extrusion, strong layer adhesion, low warping, and consistent print quality for detailed and durable prints.	Filament Type: PLA / ABS / PETG Filament Diameter: 1.75mm Color: Black Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • 1.75mm filament • FDM filament • 3D printer material • black filament • Spool
	COM-00001-C	3D Printing Filament	CO - Consumables	Creality, eSUN, Hatchbox	The 1.75mm Yellow 3D Printing Filament is a material used in FDM/FFF 3D printers for prototyping and model making. It provides smooth extrusion, strong layer adhesion, low warping, and consistent print quality. It is commonly used for robotics, enclosures, mechanical parts, DIY fabrication, and product development.	Filament Type: PLA / ABS / PETG Filament Diameter: 1.75mm Color: Yellow Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • 1.75mm filament • FDM filament • 3D printer material • yellow filament • Spool
	COM-00001-D	3D Printing Filament	CO - Consumables	Creality, eSUN, Hatchbox	The 1.75mm Blue 3D Printing Filament is a material used in FDM/FFF 3D printers for prototyping and model making. It offers smooth extrusion, strong layer adhesion, low warping, and consistent print quality. It is commonly used for robotics, enclosures, mechanical parts, DIY fabrication, and product development.	Filament Type: PLA / ABS / PETG Filament Diameter: 1.75mm Color: Blue Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • 1.75mm filament • FDM filament • 3D printer material • blue filament • Spool
	COM-00002-A	3D Printing Filament	CO - Consumables	eSUN	The 2.85mm White 3D Printing Filament is a material used in FDM/FFF 3D printers for prototyping and model making. It provides smooth extrusion, strong layer adhesion, low warping, and consistent print quality. It is commonly used for robotics, enclosures, mechanical models, DIY fabrication, and industrial design projects.	Filament Type: PLA / ABS / PETG Filament Diameter: 2.85mm Color: White Spool Weight: 750g – 1kg Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • white filament • FDM filament • 3D printer material • 2.85mm filament
	COM-00002-B	3D Printing Filament	CO - Consumables	eSUN	The 2.85mm Black 3D Printing Filament is a material used in FDM/FFF 3D printing for prototyping and model making. It offers smooth extrusion, strong layer adhesion, low warping, and consistent print quality. It is commonly used for robotics, enclosures, mechanical parts, DIY fabrication, and product development.	Filament Type: PLA / ABS / PETG Filament Diameter: 2.85mm Color: Black Spool Weight: 750g – 1kg Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • FDM filament • 3D printer material • black filament • 2.85mm filament

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COM-00002-C	3D Printing Filament	CO - Consumables	eSUN	The 2.85mm Yellow 3D Printing Filament is a material used in FDM/FFF 3D printers for prototyping and model making. It offers smooth extrusion, strong layer adhesion, low warping, and consistent print quality. It is commonly used for robotics, educational models, enclosures, DIY fabrication, and product development.	Filament Type: PLA / ABS / PETG Filament Diameter: 2.85mm Color: Yellow Spool Weight: 750g – 1kg Printing Temperature: 190°C – 220°C Heated Bed Temperature: 0°C – 60°C	3D filament • PLA filament • FDM filament • 3D printer material • yellow filament • 2.85mm filament
	COM-00002-D	3D Printing Filament	CO - Consumables	eSUN	The 2.85mm Blue 3D Printing Filament is a material used in FDM/FFF 3D printers for prototyping and model making. It offers smooth extrusion, strong layer adhesion, and consistent print quality. It is commonly used for robotics, engineering models, enclosures, DIY projects, and product development.	Filament Type: PLA / ABS / PETG Filament Diameter: 2.85mm Color: Blue Spool Weight: 750g – 1kg Printing Temperature: 190°C – 220°C	3D filament • PLA filament • FDM filament • 3D printer material • blue filament • 2.85mm filament
	EDA-00002-A	Alligator Cable	MM - Mechanical Module	Generic / OEM, KEYESTUDIO	10-pin jumper wire set featuring insulated alligator (crocodile) clips on one end and female Dupont connectors on the other. Designed for quick and secure temporary electrical connections in DIY projects, prototyping, and laboratory testing. Widely used in school physics labs, breadboard testing, circuit assembly, and component holding during soldering.	Item Type: Electronics Accessory Jumper Type: Female Clip Length: 22.6 mm Cable Length: 20 cm Material: Copper with Plastic Insulation Shipping Weight: 0.04 kg Shipping Dimensions: 7 × 4 × 2 cm	Alligator Clip Wire • Dupont Jumper Wire • 10 Pin Jumper • Crocodile Clip Cable • 20cm Test Lead
No Image	EDD-00001-A	Laser Diode Module	ED - Electronic Device	OSRAM, Sharp, Rohm, Mitsubishi, Generic	The Mini 650nm 6mm 5mW Laser Dot Diode Module is a compact red laser emitter used in electronics and robotics projects. It operates on 3–5V DC and produces a focused laser dot. It is commonly used for alignment, sensing experiments, and Arduino-based educational and DIY projects.	Item Type: Laser Module Voltage Rating (V): 5 Weight (g): 2 Operating Temperature (°C): -10 to 50 Rated Power (mW): 5mW Wavelength (nm): 650	laser diode • laser • light emitter • optical • semiconductor • electronic device
	EDD-00003-A	RGB LED Module	ED - Electronic Device	ED Series / XINGLIGHT, XINGLIGHT	5mm RGB LED module with a common cathode configuration and transparent lens for vibrant multi-color illumination. Combines red, green, and blue LEDs in a single through-hole package, enabling a wide range of colors through color mixing. Ideal for indicator panels, Arduino projects, DIY electronics, decorative lighting, visual feedback systems, and educational applications.	Manufacturer: XINGLIGHT Model No.: XL-A524SURSYGC Package: Plugin, D = 5mm Forward Current (mA): 20 Color Temperature: - Peak Wavelength (nm): 640 (Red) 572 (Green: Yellow) Luminous Intensity (mcd): 600 (Red) 550 (Green: Yellow) Lens Color: Colorless Transparent Diode Configuration: Common Cathode Wavelength – Dominant (nm): 635–640 (Red) 565–575 (Green: Yellow) Operating Temperature (°C): -20 ~ +85 Illumination Color: Red, Green-Yellow Viewing Angle: 30° Lamp Holder Type: 5mm Round Head Power (mW): 50 Forward Voltage (Vf): 2.3V (Red) 2.4V (Green: Yellow) Mounting Type: Through Hole Compliance: RoHS	RGB LED • 5mm LED • Common Cathode LED • Indicator LED • Through Hole LED
No Image	EDD-00004-A	7 Segment Display	ED - Electronic Device	Lite-On Technology, Kingbright, Generic / OEM	The 0.56" 1-Digit 7-Segment LED Display is a single-digit numeric display (0–9) using seven LED segments. It has a common cathode configuration with bright visibility. It is widely used in counters, clocks, meters, Arduino projects, and embedded systems.	Model: 7 Segment LED Display Digit Count: 1 Digit Display Size: 0.56 Inch Configuration Type: Common Cathode Emitting Color: Red Face Color: Black Number of Pins: 10 Forward Voltage (V): 1.8 – 2.2 (Typical for Red LED) Forward Current (mA): 20 (Typical) Mounting Type: PCB Through Hole Characteristics: High Brightness, Low Current Consumption, Easy to Use Length (Inch): 0.56 Shipping Weight: 0.02 kg Shipping Dimensions (L × W × H cm): 6 × 4 × 2	Arduino Compatible • 0.56" 7-Segment • 1 Digit Display • Red LED • Common Cathode • 5161AS • Through Hole • Numeric Display
	EDD-00004-B	7 Segment Display	ED - Electronic Device	Kingbright, Lite-On, Everlight, Broadcom	The Single Digit Common Anode 7-Segment Display is an LED display used to show numeric digits in electronic circuits. It offers bright, low-power number display and is easy to interface with microcontrollers. It is commonly used in Arduino projects, counters, timers, clocks, calculators, and control systems.	Display Type: 1 Digit 7 Segment LED Display Configuration: Common Anode Operating Voltage: 1.8V – 2.2V per Segment Number of Pins: 10 Pins Digit Height: 0.36 Inch – 0.56 Inch	Numeric Display • 7 segment display • common anode display • single digit display • LED display

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EDD-00005-B	Voltage Regulator	ED - Electronic Device	Texas Instruments, STMicroelectronics, ON Semiconductor, Fairchild Semiconductor	The LM7812 Voltage Regulator is a fixed-output regulator that provides a stable 12V DC supply from a higher input voltage. It includes built-in thermal overload and short-circuit protection for safe operation. It is widely used in power supplies, robotics, Arduino projects, communication modules, and embedded systems.	Device Type: Linear Voltage Regulator Output Voltage: 12V DC Package Type: TO-92 Input Voltage Range: 14V – 30V Output Current: Up to 100mA	voltage regulator • TO-92 regulator • linear regulator • power supply IC • LM7812 • 12V regulator
	EDK-00003-A	Transistor Kit	ED - Electronic Device	ON Semiconductor, Fairchild Semiconductor, Toshiba, NXP Semiconductors	The TO-92 Transistor Kit is a collection of commonly used NPN and PNP transistors in the TO-92 package for switching, amplification, and signal processing. It is ideal for prototyping, circuit development, Arduino projects, robotics, sensor interfacing, motor control, educational electronics, and DIY applications.	Package Type: TO-92 Transistor Types: NPN and PNP Operating Voltage: Up to 60V Current Rating: Up to 800mA Current Rating: Up to 800mA	transistor kit • TO-92 transistor • NPN transistor • PNP transistor • semiconductor kit • switching transistor
	EDM-00001-A	Tactile Switch	ED - Electronic Device	OMRON, E-Switch	This tactile push button switch kit includes 12x12x7.3mm momentary ON-OFF switches for reliable circuit input. Rated for 12V DC and 120mA, they provide good tactile feedback. The kit includes 25 color-coded keycaps and a storage box, making it ideal for Arduino projects, prototyping, DIY electronics, and educational use.	Item Type: Micro Switch Model: Tactile Push Button Switch Operation Mode: ON-OFF Contact Type: Momentary Current Rating: 120mA Operating Voltage: 12V DC Switch Type: Push Button Material: Metal and Plastic Mounting Type: Surface Mount Button Size (mm): 12x12x7.3 Operating Temperature (°C): -25 to +70 Lifespan: ~1000 Cycles Box Dimensions (mm): 127.1 × 68.3 × 21.9 Weight (g): 55 Shipping Weight: 0.06 kg Shipping Dimensions (L × W × H): 13 × 7 × 3 cm	Tactile Switch • Push Button • 12x12mm Switch • Momentary Switch • Arduino Button Kit
	EDM-00002-A	Power switch	ED - Electronic Device	C&K, Omron	The Power Switch is a mechanical device used to control electrical power in circuits and electronic equipment. It provides reliable ON/OFF operation for safely connecting or disconnecting power. Commonly used in power supplies, embedded systems, control panels, DIY electronics, and consumer devices.	Switch Type: SPST (Single Pole Single Throw) Rated Voltage: 125V – 250V AC / 12–24V DC Rated Current: 3A – 10A	toggle switch • rocker switch • power switch • on off switch • SPST switch • electrical switch
	EDM-00002-B	Power switch	ED - Electronic Device	C&K, Omron	The On/Off Power Switch is a mechanical switch used to control the flow of electrical power in electronic circuits and devices. It provides a simple and reliable way to turn equipment ON or OFF. Commonly used in power supplies, embedded systems, control panels, DIY electronics, and consumer devices for convenient manual power control.	Switch Type: SPST (Single Pole Single Throw) Rated Voltage: 125V – 250V AC / 12–24V DC Rated Current: 3A – 10A	toggle switch • rocker switch • power switch • SPST switch • electrical switch • on/off switch
	EDM-00003-A	DPDT Toggle Switch	ED - Electronic Device	C&K, E-Switch, Omron	The DPDT (Double Pole Double Throw) Toggle Switch is a mechanical switch used to control two separate circuits and switch each between two output paths. It is commonly used for polarity reversal, motor direction control, signal routing, power selection, automation, robotics, and DIY electronics projects.	Switch Type: DPDT (Double Pole Double Throw) Number of Pins: 6 Pins Rated Voltage: 125V – 250V AC / 12–30V DC Rated Current: 3A – 6A	toggle switch • DPDT switch • 6 pin switch • polarity reversing switch • control switch
	EDM-00005-A	Prototype Board	ED - Electronic Device	MWduino / Generic	Complete prototyping kit with 400-point solderless breadboard and T-type GPIO breakout module. Includes 40-pin flat ribbon cable for clean and organized Raspberry Pi GPIO access. Ideal for Raspberry Pi projects, circuit prototyping, and educational experimentation.	Item Type: Cable Model: GPIO Compatibility: Raspberry Pi 3 Model B/B+ T: Connector Dimensions (mm): 72 × 59 × 12 T: Connector Weight (g): 13 Pitch (mm): 2.54 Cable Length (cm): 20 (Flat Ribbon) No. of Pins: 40 Width of Cable (cm): 5.5 Additional Specs (mm): 84 × 55 × 8.5 (L × W × H) No. of Tie Points: 400 Weight (g): 40 Material: ABS Plastic Shipping Weight: 0.06 kg Shipping Dimensions (L × W × H): 10 × 7 × 7 cm	Breadboard 400 Point • GPIO Breakout Board • Raspberry Pi GPIO • T-Type Adapter • 40 Pin Ribbon Cable
No Image	EDM-00003-B	Breadboard Mini	ED - Electronic Device	BusBoard Prototype, Twin Industries, Elegoo, SunFounder, Generic	The Mini Solderless Breadboard (170 Tie Points) is a compact prototyping board used for building circuits without soldering. It allows easy component placement and quick circuit testing. It is commonly used in Arduino projects, electronics experiments, and educational kits.	Item Type: Breadboard No. of Points: 170 Tie Points: 170 Material: ABS Mounting holes: M2 Length (mm): 48 Width (mm): 35 Height (mm): 9 Weight (g): 14	testing • Prototyping • Electronics • breadboard • mini breadboard • pcb • solderless

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EDM-00006-A	Header Pin Strip	ED - Electronic Device	Samtec, Amphenol, Harwin, TE Connectivity, Molex	The Break-Away Header Pin Strip is a customizable PCB connector that can be cut to any length. It is used for through-hole mounting and provides flexible pin configurations for electronic circuits. It is commonly used in Arduino projects, embedded systems, shields, and prototyping applications.	Pitch Size: 2.54mm (0.1 Inch) Connector Type: Male Pin Header Number of Pins: 40 Pins Mounting Type: Through Hole Current Rating: 3A Typical	Male Header • Pin Header • PCB Connector • Arduino Header • Breakaway Header • 2.54mm Header
	EDM-00007-A	Female Header Strip	ED - Electronic Device	Samtec, Amphenol, Harwin, TE Connectivity, Molex	The 2x40 Pin Female Double Row Header Strip is a PCB connector with two rows of 40 pins used for board-to-board and module connections. It provides reliable and organized electrical connectivity and is commonly used in Arduino shields, Raspberry Pi interfaces, embedded systems, and prototyping projects.	Pitch Size: 2.54mm (0.1 Inch) Connector Type: Female Header Socket Number of Pins: 40 Pins Mounting Type: Through Hole Current Rating: 3A Typical	PCB Connector • 2.54mm Header • Female Header • Socket Header • Arduino Connector • Female Pin Header
	EDM-00008-A	Female Connector	ED - Electronic Device	Amphenol, TE Connectivity, Molex	The RJ11 4P4C Female Connector is a modular socket used for telephone and communication wiring applications. It provides a secure connection for telephone cables, modems, intercom systems, and low-speed data communication lines. It is widely used in landline networks, IoT projects, electronics prototyping, and communication systems.	Connector Type: RJ-11 4P4C Female Jack Number of Contacts: 4 Pin (4P4C) Material: Thermoplastic Housing with Metal Contacts Rated Voltage: Low Voltage Signal (	RJ11 connector • 4P4C female jack • telephone adapter • modular connector • communication jack
	EDM-00009-A	PCB Prototype Board	ED - Electronic Device	Bud Industries, Twin Industries, BusBoard Prototype Systems, Keyestudio, Generic / OEM	The 4x6 cm Universal PCB Prototype Board is a durable prototyping board used for building and testing electronic circuits. It features a HASL finish and precision drilled holes for easy soldering. It is commonly used in Arduino projects, embedded systems, and DIY electronics development.	Item Type: PCB Prototype Board Dimensions: 4 × 6 cm Length: 60 mm Width: 40 mm Board Thickness: 1.6 mm Copper Thickness: 1–4 oz Minimum Hole Size: 0.3 mm Weight (Unit): 6 g Pack Quantity: 2 Pieces Shipping Weight: 0.01 kg Shipping Dimensions: 7 × 5 × 1 cm	Double-Sided PCB • 4x6 cm • FR4 • Prototype Board • 2.54mm Pitch • DIY Electronics
	EDR-00001-470Z	Resistor - 470 Ohm	ED - Electronic Device	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	The 470 Ohm 0.25W Metal Film Resistor is a passive component used to limit current and control voltage in electronic circuits. It provides stable, precise resistance with low noise and is commonly used in LED circuits, Arduino projects, and embedded systems.	Power: 1/4 W Resistance: 47k ? Resistance Tolerance: 5% Type: Carbon Film Resistors	resistor • carbon film • 0.25w • passive • axial • 470ohm
	EDR-00002-10K0	Potentiometer	ED - Electronic Device	ED Series / Generic Compatible, Bourns, Alpha, Omega	10K? rotary potentiometer used for adjusting voltage, current, and signal levels in electronic circuits. Features smooth single-turn rotation, a durable 15mm shaft, and through-hole mounting for easy installation. Ideal for audio volume control, Arduino analog inputs, sensor calibration, circuit tuning, embedded systems, prototyping, and educational electronics projects.	Manufacturer: Generic Resistance (Ohm): 10K Tolerance (%): 20 Temperature Coefficient: ±100ppm/°C Operating Temperature (°C): -40 to 80 Mounting Type: Through Hole Shaft Type: 15mm Rotary Shaft Adjustment Type: Single Turn Length (mm): 20 Width (mm): 17 (Body Diameter) Height (mm): 24 Weight (g): 6 Shipping Weight: 0.001 kg Shipping Dimensions (L × W × H): 1 × 1 × 1 cm	10K Potentiometer • Rotary Pot • Variable Resistor • WH148 Potentiometer • 3-Pin Pot
	EDS-00006-A	IC NE 555	ED - Electronic Device	Texas Instruments, STMicroelectronics, ON Semiconductor, NXP, Generic	The NE555 Timer IC is a precision timing chip used to generate delays, pulses, and oscillations. It works in monostable and astable modes and is widely used in timers, LED flashing circuits, pulse generators, and electronics projects.	Case/Package: PDIP 8 Min Supply Voltage: 4.5 Max. Supply Voltage (V): 16 Product Type: Timers & Support Products Processor Series: NE555 No. of Timers/Counters: 1 Operating Temperature (°C): 0 to 70 Dimensions (L x W x H) mm: 9.81 x 4.57 x 6.35 Mounting Type: Through Hole	Electronics • ne555 • timer ic • oscillator • pulse generator • ic • astable
	EDT-00006-B	Force Sensor	EM - Electronic-Electrical Modules	Interlink Electronics, SparkFun Electronics, DFRobot, Adafruit Industries, Ohmite	The Force Sensitive Resistor (FSR) is a pressure sensor that changes resistance based on applied force. It detects pressure in the range of 100g to 10kg and is commonly used with voltage divider circuits. It is widely used in touch sensing, load detection, robotics, and Arduino-based projects.	Actuation Force: 0.1 N Clock Speed: 16MHz	FSR Sensor • Pressure Sensor • Force Sensitive Resistor • Square Force Sensor • Touch Sensor

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EDT-00007-A	Flex Sensor	ED - Electronic Device	Spectra Symbol, SparkFun, Adafruit, Interlink Electronics, Generic	The 2.2? Flex Sensor is a bend-detecting resistor that changes resistance when flexed. It is used to measure bending or motion and is commonly used in robotics, wearables, gaming controllers, and motion-sensing applications.	Bend Resistance: minimum 20K Ohms ±30% (@ 180° pinch bend) Flat Resistance: 10K Ohms ±30% Flex length: 2.2 inch (5.6 cm) Power: 0.5 Watts continuous Length: 7 cm	Electronics • flex sensor • bend sensor • sensor • analog • resistance • wearable
	EMA-00001-A	I2C LCD Display	EM - Electronic-Electrical Modules	MWduino / Generic, KEYESTUDIO, SunFounder	16x2 character LCD module with an integrated I2C interface for simplified wiring and reduced pin usage. Features a blue backlight with white characters for clear, high-contrast visibility. Ideal for Arduino, Raspberry Pi, microcontroller projects, embedded systems, sensor monitoring, and applications requiring a compact and easy-to-read data display.	Model: Other LCD Model No.: LCD1602 Display Type: 16 × 2 Character LCD Backlight Color: Blue Character Color: White I2C Address: 0x27 Input Voltage (V): 5 Length (mm): 36 Width (mm): 80 Height (mm): 18 Weight (g): 35 Shipping Weight: 0.037 kg Shipping Dimensions (L × W × H): 8 × 5 × 3 cm	LCD1602 • 16x2 LCD • I2C LCD Display • Arduino Display • Character LCD Module
	EMA-00003-E	Coin Battery	EM - Electronic-Electrical Modules	Panasonic, Maxell, Energizer, Sony	The CR2032 3V Lithium Coin Battery is a compact, long-lasting power source used in small electronic devices like watches, calculators, remotes, toys, and embedded systems. It provides a stable 3V output and is widely used in low-power applications due to its long shelf life and reliability.	Battery Type: Lithium Coin Cell Battery Size: CR2025 Chemistry: Lithium Manganese Dioxide (LiMnO?) Nominal Voltage: 3 V Nominal Capacity: 165 mAh Diameter: 20 mm Height: 2.5 mm Termination Style: Pressure Contacts Operating Temperature: −30°C to +60°C Weight (Unit): 2.3 g Shipping Weight: 0.008 kg Shipping Dimensions: 9.2 × 7.5 × 1 cm	CR2025 Battery • 3V Coin Cell • Lithium Battery • Panasonic Battery • Button Cell
	EMA-00004-A	LED Matrix	EM - Electronic-Electrical Modules	Analog Devices, Keystudio, SparkFun	The 8x8 LED Dot Matrix Display with MAX7219 Driver features a 64-LED matrix and an integrated MAX7219 controller for easy serial communication. It reduces microcontroller pin usage and is used to display text, symbols, patterns, and animations in Arduino, ESP32, Raspberry Pi, and embedded projects.	Product Type: LED Matrix Display Module Matrix Size: 8 × 8 Driver IC: MAX7219 Number of LEDs: 64 LEDs Operating Voltage: 5V DC	MAX7219 LED Matrix Module • 8x8 LED Matrix Display • MAX7219 Dot Matrix • Arduino LED Matrix
No Image	EMA-00006-B	Passive Buzzer	EM - Electronic-Electrical Modules	ED Series / Generic Compatible, KEYESTUDIO	Passive buzzer module for generating variable tones using PWM or frequency control. Operates on 1.5V–15V DC and produces sound in the 1.5–2.5 kHz range. Ideal for alarms, alerts, educational projects, Arduino applications, and microcontroller-based sound generation. Compact, reliable, and easy to interface with electronic circuits and development boards.	Model: Passive Buzzer Module Operating Voltage (VDC): 1.5 – 15 Max Operating Current (mA): 25 Tone Generator Frequency Range (kHz): 1.5 – 2.5 Mounting Type: PCB Mount Pin Pitch: 2.54 mm Compatibility: Arduino / Microcontrollers Length (mm): 15 Width (mm): 19.7 Height (mm): 10 Weight (g): 1 (approx.) Shipping Weight: 0.01 kg Shipping Dimensions (L × W × H): 6 × 4 × 2 cm	Passive Buzzer • KY-006 Module • Arduino Buzzer • PWM Buzzer • Sound Module
	EMA-00008-A	1 Channel Relay	EM - Electronic-Electrical Modules	Single Relay, Generic / OEM	The Single Channel 12V Relay Module is used to control high-voltage AC/DC devices using low-voltage microcontrollers. It supports high/low-level triggering and includes LED indicators. It is commonly used in home automation, IoT, and motor control applications.	Model: Relay Module Number of Channels: 1 Operating Voltage (VDC): 12 Trigger Type: High-Level / Low-Level Trigger Relay Contact Rating (AC): 10A @ 250V AC Relay Contact Rating (AC Alternate): 15A @ 125V AC Contact Type: COM, NO (Normally Open), NC (Normally Closed) Interface: 2.54 mm Header Pins Output Connection: 3-Pin Screw Terminal Indicators: Power LED + Relay Status LED Length (mm): 50 Width (mm): 25 Height (mm): 20 Weight (g): 16 Shipping Weight: 0.025 kg Shipping Dimensions (L × W × H cm): 7 × 4 × 3	Arduino Compatible • 12V Relay Module • Single Channel Relay • High/Low Trigger • Sngle SRD-12VDC-SL-C • SPDT Relay • 10A 250VAC • IoT Switching Module
	EMA-00008-B	2 Channel Relay	EM - Electronic-Electrical Modules	Songle, Keyes, SunFounder, Elegoo, Generic	The 5V 2 Channel Relay Module is used to control high-power AC and DC devices using low-power microcontrollers like Arduino. It supports up to 10A switching per channel and includes LED indicators for status. It is commonly used in home automation, IoT systems, and industrial control applications.	No. of Channels: 2 Operating Temperature Range: -40 to 85 °C Operating Voltage: 2.5 ~ 5.5 V (DC) Switching Voltage(AC): 240V@10A Switching Voltage(DC): 30V@10A Trigger Current: 20 mA Trigger Voltage: 5V (DC) Length: 4.3 cm Height: 1.7 cm Width: 4.3 cm	arduino • module • 5v • relay module • 2 channel • switching • control

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
No Image	EMC-00003-A	NodeMcu	EM - Electronic-Electrical Modules	Espressif Systems, Ai-Thinker, NodeMCU	The ESP8266 NodeMCU CH340 board is a WiFi-enabled microcontroller based on the ESP8266 chip for IoT applications. It offers onboard processing, GPIO support, and built-in wireless connectivity. It is widely used in IoT projects, smart devices, automation systems, and wireless sensor applications.	Processor: L106 32 bit Processor speed: 80MHz to 160MHz Flash memory: 4MB Analog to digital: 1 input with 1024 resolution Maximum concurrent TCP connection: 5 GPIOs: 17 Transfer rate: 110 Kbps to 460800 Kbps Input voltage supply: 4.5V to 9V Communication interface voltage: 3.3V Current consumption: 10uA-170mA	NodeMCU • ESP8266 • WiFi Module • IoT Development Board • ESP8266EX • Wireless Module
	EMC-00004-A	Bluetooth Module	EM - Electronic-Electrical Modules	HC Series / Generic Compatible, Waveshare, KEYESTUDIO, SunFounder	The HC-05 Bluetooth Module is a 6-pin wireless communication device used for UART-based data transfer between microcontrollers and Bluetooth-enabled devices. Operating in the 2.4GHz ISM band with GFSK modulation, it supports both Master and Slave modes. Featuring AT command configuration and an onboard push button for AT mode access, it is ideal for wireless control, automation, and IoT projects.	Operating Voltage: 3.6V – 6V DC Input Current: 50 mA Operating Frequency: 2.4 GHz ISM Band Modulation Type: GFSK (Gaussian Frequency Shift Keying) Emission Power: 4 dBm (Class 2) Receiver Sensitivity: -84 dBm at 0.1% BER Maximum Range: 10 meters (typical) Interface Pins: EN/KEY, VCC, GND, TXD, RXD, STATE AT Command Support: Yes Onboard Button: Yes (AT Mode Selection) Length (mm): 43 Width (mm): 16.5 Height (mm): 7 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (cm): 5 × 3 × 1	HC-05 • Bluetooth Module • UART Bluetooth • 6-Pin Bluetooth • Master Slave Module • Arduino Bluetooth
No Image	EMC-00006-A	GSM-GPRS Module	EM - Electronic-Electrical Modules	SIMCom, DFRobot, Waveshare	The SIM800L GSM/GPRS Module is a compact GSM modem used for SMS, voice calls, and GPRS internet connectivity. It supports quad-band GSM networks and TCP/IP communication. It is widely used in IoT projects, tracking systems, remote monitoring, automation, and embedded wireless communication.	IC Chip: SIM800L Input Voltage: 3.4V ~ 4.4V Peak Current: 2 A	SIM800L • GSM Module • GPRS Module • SMS Module • IoT Module • Arduino GSM • ESP8266 GSM
No Image	EMC-00006-B	GSM Module	EM - Electronic-Electrical Modules	SIMCom, DFRobot, Itead Studio	The SIM900A GSM Module is a wireless communication module used for SMS, voice, and data applications over GSM networks. It supports UART communication and SIM card integration for microcontrollers like Arduino. It is widely used in IoT systems, remote monitoring, automation, and embedded communication projects.	Frequency bands: Dual-band GPRS connectivity: GPRS multi-slot class 10 (default) , GPRS multi-slot class 8 (option) Operating Temperature Range: -30 to 80 °C Supply Voltage: 3.4 – 4.5 V Dimensions (LxWxH): 8.5x5.7x2cm (approx)	GSM Module • GPRS Module • SMS Module • IoT Module • Arduino GSM • SIM900A
No Image	EMC-00008-A	IR Receiver module	EM - Electronic-Electrical Modules	Vishay Semiconductors, Sharp Corporation, Keyestudio, DFRobot, SparkFun Electronics	The KY-022 IR Receiver Module is a 38kHz infrared sensor used to detect and decode signals from IR remote controls. It provides a digital output with an indicator LED when an IR signal is received. It is commonly used in Arduino projects, robotics, home automation, and remote-control decoding applications.	Current consumption: 1.5mA peak Frequency: 38kHz Operating Voltage: 3.3V to 5V Pulse Duration: 400µs to 800µs Range: 17m Wavelength: 940 nm	IR Receiver • Infrared Sensor • TSOP1838 • Remote Receiver • Arduino IR Sensor • 38kHz IR Module • IR Decoder
	EMS-00002-A	Temp Humidity Sensor	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Digital temperature and humidity sensor module with calibrated single-wire serial output for easy interfacing. Features an onboard pull-up resistor and LED status indicator for reliable operation. Suitable for weather stations, environmental monitoring, smart home systems, Arduino projects, and IoT applications requiring accurate temperature and humidity measurements.	Item Type: Sensor Model: DHT11 Temperature and Humidity Sensor Measuring Temperature Range (°C): 0 – 50 Temperature Accuracy: ± 2 °C Humidity Range: 20 – 95 % RH Humidity Accuracy: ± 5 % RH Resolution: 16 bit Output Form: Digital Output (Single Wire Serial) Operating Voltage (VDC): 3 – 5 Operating Current (mA): ? 2.5 Dimensions (L × W × H mm): 31 × 14 × 7.5 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (L × W × H cm): 5 × 5 × 2	DHT11 • Temperature Sensor • Humidity Sensor • Digital Temp Sensor • Arduino Climate Sensor
	EMS-00003-C	Accelerometer module	EM - Electronic-Electrical Modules	Freescall Semiconductor, DFRobot, Elecrow	The MMA7361 Accelerometer Module is a low-power 3-axis analog accelerometer used to measure acceleration, tilt, vibration, orientation, and motion along the X, Y, and Z axes. Based on the Freescale/NXP MMA7361L MEMS sensor, it provides analog voltage outputs proportional to acceleration values. It is widely used in robotics, motion tracking, gaming devices, and Arduino-based projects.	Product Type: 3-Axis Accelerometer Module Model: MMA7361L Sensor Type: MEMS Accelerometer Axes: X, Y, Z Operating Voltage: 3.3V – 5V DC	Tilt Sensor Module • MMA7361 Accelerometer • Triple Axis Accelerometer • 3-Axis Accelerometer Module

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EMS-00004-C	Microphone Module	EM - Electronic-Electrical Modules	Analog Devices / Maxim Integrated, SparkFun, DFRobot, Keyestudio	The MAX4466 Electret Microphone Module is a low-noise sound sensor with an inbuilt amplifier for detecting and monitoring audio signals. It uses an electret microphone with the MAX4466 op-amp to provide clear analog output. It is commonly used in voice detection, sound level monitoring, robotics, and Arduino/ESP32 projects.	Product Type: Electret Microphone Module Main IC: MAX4466 Output Type: Analog Operating Voltage: 2.4V – 5.5V DC	MAX4466 Microphone Module • Electret Microphone Amplifier • Sound Sensor Module • Audio Detection Sensor
	EMS-00006-A	PIR Sensor	EM - Electronic-Electrical Modules	HC, DFRobot, SparkFun, Keyestudio	The PIR Motion Sensor is a passive infrared detection module used to detect human movement and body heat by sensing changes in infrared radiation. The commonly used HC-SR501 PIR sensor combines a pyroelectric infrared sensor with a Fresnel lens to detect motion within its sensing range. It is widely used in security systems, automatic lighting, smart homes, robotics, and Arduino projects.	Product Type: PIR Motion Sensor Model: HC-SR501 Sensor Type: Passive Infrared Operating Voltage: 5V – 20V DC Detection Distance: 3 – 7 meters	Motion Detection Sensor • PIR Motion Sensor • HC-SR501 PIR Sensor • Human Motion Sensor
No Image	EMS-00007-A	Temperature Sensor	EM - Electronic-Electrical Modules	Maxim Integrated, DFRobot, SparkFun	The DS18B20 Temperature Sensor Module is a digital temperature sensor that uses the 1-Wire communication protocol for accurate readings. Developed by Dallas Semiconductor, it provides calibrated digital output with high precision and supports multiple sensors on a single data line. It is widely used in weather stations, automation systems, industrial monitoring, and Arduino projects.	Product Type: Digital Temperature Sensor Model: DS18B20 Communication Protocol: 1-Wire Operating Voltage: 3V – 5.5V DC Temperature Range: -55°C to +125°C Accuracy: ±0.5°C	DS18B20 Temperature Sensor • Waterproof Temperature Sensor • Digital Temperature Sensor • One Wire Temperature Sensor
No Image	EMS-00010-G	MQ-135 Sensor	EM - Electronic-Electrical Modules	Hanwei Electronics, Zhengzhou Winsen Electronics, Futurlec	The MQ-135 Air Quality Sensor Module is used to detect harmful gases and monitor air pollution levels. It changes its conductivity based on gas concentration and provides an analog output. It is sensitive to gases like ammonia, benzene, smoke, and other pollutants. It is widely used in air quality monitoring, IoT systems, and environmental safety projects.	Model: MQ-135 Detecting range: 100ppm to 1000ppm Operating current: 150 mA Operating Voltage: 5 V Length: 3.2 cm Height: 2.7 cm Width: 2 cm	Air Quality Sensor • MQ135 • Ammonia Sensor • NOx Sensor • CO2 Sensor • Smoke Sensor
	EMS-00012-A	Color Sensor	EM - Electronic-Electrical Modules	ams-OSRAM, ams-OSRAM, ams-OSRAM, Generic Electronics	The TCS3200 Color Sensor Module is an RGB color detection sensor used to identify and measure colors based on reflected light intensity. It uses a light-to-frequency converter IC and photodiodes with onboard LEDs for accurate sensing. It is commonly used in robotics, color sorting, automation, and Arduino projects.	Product Type: RGB Color Sensor Model: TCS3200 / TCS230 Sensor Type: Light-to-Frequency Converter Operating Voltage: 2.7V – 5.5V DC	Arduino Color Sensor • Color Detection Module • TCS3200 Color Sensor • RGB Color Sensor • TCS230 Sensor • RGB Recognition Module • ESP32 Color Sensor • Light Frequency Sensor
	EMS-00012-B	Color Sensor Module	EM - Electronic-Electrical Modules	ams-OSRAM, ams-OSRAM, ams-OSRAM, Generic Electronics	The TCS3200 Color Sensor Module is an RGB color detection sensor used to identify and measure colors based on reflected light intensity. It uses a light-to-frequency converter IC and photodiodes with onboard LEDs for accurate sensing. It is commonly used in robotics, color sorting, automation, and Arduino projects.	Product Type: RGB Color Sensor Model: TCS3200 / TCS34725 Sensor Type: Light-to-Frequency Converter Operating Voltage: 2.7V – 5.5V DC	TCS3200 Sensor • RGB Sensor • Color Sensor • TCS230 Module • Arduino Color Sensor • ESP32 RGB Sensor • Color Detection Module
	EMS-00015-B	3×4 Membrane Keypad	EM - Electronic-Electrical Modules	Adafruit, DFRobot, SparkFun, Keyestudio	The 3×4 12-Key Membrane Keypad is a compact matrix input device used with Arduino, ESP32, Raspberry Pi, and other microcontrollers. It has 12 buttons in a 4×3 telephone-style layout, reducing GPIO usage while allowing easy user input. It is commonly used in password systems, calculators, access control, and embedded projects.	Product Type: Membrane Matrix Keypad Key Layout: 3×4 Matrix Number of Keys: 12 Operating Voltage: 3V – 35V DC Connector Type: 7-pin Header	12 Key Matrix Keypad • Membrane Switch Keypad • Arduino Keypad • 3x4 Membrane Keypad • Numeric Keypad Module • 4x3 Matrix Keyboard • Telephone Style Keypad • Matrix Input Module

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EMS-00015-C	4x4 Keypad	EM - Electronic-Electrical Modules	Adafruit, Keystudio, DFRobot, SparkFun	The 4×4 / 4×3 Membrane Keypad is a thin, flexible input device used with Arduino, ESP32, Raspberry Pi, and other microcontrollers. It uses a row-column matrix to reduce GPIO usage while providing multiple button inputs. It is commonly used in password systems, calculators, access control, and embedded projects.	Product Type: Membrane Matrix Keypad Key Layout: 4×4 / 4×3 Number of Keys: 12 or 16 Operating Voltage: 3V – 35V DC Connector Type: 7-pin / 8-pin Header	4x4 Membrane Keypad • 12 Key Matrix Keypad • Membrane Switch Keypad • Matrix Keyboard Module • Arduino Keypad • Numeric Input Module • 4x3 Matrix Keypad • Keypad Module
	EMS-00017-A	LDR Module	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO	The LDR Module detects ambient light intensity and provides a digital output based on the surrounding brightness level. It features an onboard potentiometer for adjusting sensitivity and threshold settings. Ideal for automatic lighting systems, day/night detection, Arduino projects, smart automation, security systems, and other light-controlled electronic applications.	Model: Light Dependent Resistor Module Operating Voltage (V): 3.3 – 5 Operating Current (mA): 15 Output Type: Digital (DO) Adjustable Threshold: Yes (via Potentiometer) Sensor Type: Photoresistor (LDR) Mounting Hole: M3 Indicator LEDs: Power LED, Status LED Pin Configuration: VCC, GND, DO Length (mm): 36 Width (mm): 14 Height (mm): 8 Weight (g): 3 Shipping Weight: 0.005 kg Shipping Dimensions (L × W × H): 4 × 3 × 2 cm	LDR Module • Light Sensor • Photoresistor Module • LM393 Sensor • Arduino Light Sensor
	EMS-00026-A	Magnetometer Module	EM - Electronic-Electrical Modules	Honeywell, ITEAD Studio, DFRobot, Adafruit, SparkFun	The HMC5883L Triple Axis Compass Magnetometer Module is a 3-axis digital compass sensor used in navigation, robotics, drones, GPS systems, and Arduino projects. It communicates via I2C and measures magnetic field strength along the X, Y, and Z axes. It provides accurate heading and orientation data for motion tracking and autonomous applications.	Product Type: Triple Axis Magnetometer Sensor Model: HMC5883L Number of Axes: 3 Axis Communication Interface: I2C Operating Voltage: 3.3V – 5V ADC Resolution: 12-bit	HMC5883L Sensor • Magnetometer Module • Compass Sensor • Triple Axis Compass • GY-271 Sensor • GY-273 Module • Arduino Compass Sensor
	EMX-00001-A	Arduino Uno R3	EM - Electronic-Electrical Modules	Arduino, Elegoo, HiLetgo, Keystudio	The Arduino Uno R3 is a microcontroller development board based on the ATmega328P, designed for building interactive electronics projects. It features 14 digital I/O pins, 6 analog inputs, a 16 MHz clock, USB interface, and operates at 5V. It is widely used in education, prototyping, robotics, and embedded system development.	Board Type: Uno With Cable: Yes Operating Voltage: 5 V Input Voltage Range: 6 – 20 V Analog I/O Pins: 6 Digital I/O Pins: 14 (6 × PWM) DC Current per I/O Pin: 40 mA Clock Speed: 16 MHz SRAM: 2 KB EEPROM: 1 KB Flash Memory: 32 KB Dimensions (L × W × H): 75 × 54 × 12 mm Weight: 28 g (without cable), 54 g (with cable)	ATmega328P • 5 V Board • 16 MHz Crystal • USB Interface • Microcontroller • Educational Kit • Open-Source Hardware • Breadboard Compatible
	EQE-00002-A	Digital Multimeter	EQ - Equipment/Instrument	Generic / OEM, YX-360, Mastech, Victor, Pro'sKit	Compact Digital Multimeter for everyday electrical testing. Measures AC/DC voltage, DC current, resistance, diode, continuity, transistor hFE, battery condition, and square wave output. Features an easy-to-read LCD display for accurate readings. Ideal for students, hobbyists, laboratories, DIY projects, and technicians for troubleshooting, testing, and educational applications.	Item Type: Multimeter Model Type: Digital Multimeter (DT830D Type) Probe Length: 60 cm Length: 120 mm Width: 70 mm Height: 27 mm Weight: 160 g Shipping Weight: 0.18 kg Shipping Dimensions: 15 × 8 × 3.5 cm	DT830D • Digital Multimeter • AC/DC Tester • LCD Display • VOM
	EQM-00001-A	3D Printer	EQ - Equipment/Instrument	Tiertime Official Website, Cetus 3D Official Website, UP3D / Tiertime, Tiertime Europe	The Cetus MK3 is a compact FDM/FFF 3D printer used for education, prototyping, STEM labs, and hobby projects. It features Wi-Fi connectivity, touchscreen control, and support for multiple nozzle sizes with modular upgrades. It delivers reliable print quality and supports PLA, PETG, TPU, and other filaments, making it ideal for learning and rapid prototyping.	Product Type: FDM / FFF 3D Printer Model: Cetus MK3 Printing Technology: MEM / FDM Build Volume: 180 × 180 × 180 mm Layer Resolution: 50 – 350 Micron Nozzle Sizes: 0.2 / 0.4 / 0.6 mm Filament Diameter: 1.75 mm	FDM Printer • Educational 3D Printer • Cetus MK3 • Cetus 3D Printer • DIY 3D Printer • Compact 3D Printer • Tiertime Printer
	EQM-00001-B	3D Printer	EQ - Equipment/Instrument	FlashForge USA, Inventor Technologies, Robotbanao	The FlashForge Adventurer 3C is a compact FDM 3D printer used for education, prototyping, STEM labs, and hobby projects. It features a removable heated build plate, enclosed chamber, Wi-Fi connectivity, touchscreen control, and easy nozzle replacement. It supports PLA, ABS, and PETG filaments and offers reliable, user-friendly 3D printing.	Product Type: FDM 3D Printer Model: Adventurer 3C Printing Technology: FDM (Fused Deposition Modeling) Build Volume: 150 × 150 × 150 mm Nozzle Diameter: 0.4 mm Max Nozzle Temperature: 240°C Filament Diameter: 1.75 mm	3D Printer • FlashForge Printer • Adventurer 3C • FDM Printer • DIY Printer • STEM Printer • Educational 3D Printer

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	MMB-00001-A	Cardboard Box	MM - Mechanical Module	Packman Packaging, Corrugated Box India, Uline, Pragati Pack	Big cardboard boxes are strong corrugated containers used for shipping, storage, moving, and organizing items like tools, electronics kits, robotics parts, and DIY supplies. They are lightweight, durable, and provide good protection during transport. Made from recyclable materials, they are available in different sizes and are ideal for home, workshop, and commercial use.	Product Type: Corrugated Cardboard Box Box Size: Large Material: Corrugated Cardboard Ply Type: 3 Ply / 5 Ply	Cardboard Box • Corrugated Box • Packaging Box • Storage Carton • Shipping Box • Moving Box • DIY Storage Box
	MMB-00002-A	Compartment Box	MM - Mechanical Module	Stanley, Pro'sKit, Tactix, Deli	The 8-compartment storage box is a durable organizer for storing electronic components, motors, sensors, screws, wires, connectors, Arduino accessories, tools, and DIY hardware. It features a sturdy plastic body with a transparent lid and removable dividers for flexible storage. Ideal for workshops, labs, and DIY projects, it keeps items neatly organized and easily accessible.	Product Type: Compartment Storage Box Number of Compartments: 8 Material: Plastic / Polypropylene Box Type: Large Organizer Box Storage Items: Sensors, Screws, Components	Storage Box • Component Storage Box • Parts Organizer • DIY Storage • 8 Compartment Box • Large Organizer Box • Hardware Organizer
	MMC-00001-A	M-F Jumper Wire	MM - Mechanical Module	MWduino / Generic	20cm male-to-female jumper wires designed for flexible and reliable circuit connections. Includes 20 multi-color wires with 2.54mm male pins and female header connectors for easy interfacing. Ideal for Arduino, Raspberry Pi, sensors, modules, breadboards, prototyping, testing, and educational electronics projects.	Item Type: Jumper Wire Cable Type: Male to Female Cable Length (cm): 20 Quantity (pcs): 20 Connector Type: Male Pin ? Female Header Color Coding: Multi-color (10–20 assorted colors) Compatibility: Breadboards, Arduino, Raspberry Pi, Sensors Weight (g): 16 Shipping Weight: 0.016 kg Shipping Dimensions (L × W × H): 10 × 7.5 × 2 cm	Breadboard Wire • Arduino Wire • Prototyping Cable • Jumper Wire • Male to Female
	MMC-00001-B	M-M Jumper Wire	MM - Mechanical Module	Male-to-Male Jumper Wire (20 cm, Pack of 20)	20cm male-to-male jumper wires designed for quick and reliable circuit connections. Includes 20 multi-color flexible wires with standard 2.54mm male header pins for easy interfacing. Ideal for breadboards, Arduino, Raspberry Pi, sensors, modules, prototyping, circuit testing, and educational electronics projects.	Item Type: Jumper Wire Cable Type: Male to Male Cable Length (cm): 20 Quantity (pcs): 20 Connector Type: Male Header Pins Color Coding: Multi-color (10–20 assorted colors) Compatibility: Breadboards, Arduino, Raspberry Pi, Sensors Weight (g): 16 Shipping Weight: 0.016 kg Shipping Dimensions (L × W × H): 10.5 × 7.5 × 2 cm	Breadboard Wire • Arduino Wire • Prototyping Cable • Jumper Wire • Male to Male
	MMC-00001-C	F-F Jumper Wire	MM - Mechanical Module	TWIN INDUSTRIES	20 cm Female-to-Female jumper wires for reliable connections between pins or headers. Pack of 20 flexible, color-coded wires compatible with breadboards and Arduino projects. Ideal for prototyping, testing, educational use, and sensor connections.	Cable Type: Female to Female Cable Length (cm): 20 Quantity (pcs): 20 Connector Type: Female Header ? Female Header Color Coding: Multi-color (10–20 assorted colors) Compatibility: Breadboards, Arduino, Raspberry Pi, Sensors Weight (g): 17 Shipping Weight: 0.017 kg Shipping Dimensions (L × W × H): 10 × 7.5 × 2 cm	Female-to-Female Jumper • Breadboard Wire • Arduino Wire • Prototyping Cable • 20cm • Multi-color
	MMC-00004-A	USB A to B Cable	MM - Mechanical Module	MWduino	USB Type-A to Type-B data cable designed for Arduino UNO and other compatible development boards. Provides reliable data transfer and stable 5V power for programming, debugging, and communication. Features a compact 30cm length and durable construction, making it ideal for students, hobbyists, prototyping, embedded systems development, and educational electronics projects.	Item Type: Data Cable Color: Blue Cable Length: 30 cm USB Type: Type-A to Type-B Weight: 19 g Shipping Weight: 0.025 kg Shipping Dimensions (L × W × H): 9 × 7 × 2 cm	USB Cable • USB A to B • Arduino Cable • Printer Cable • UNO Programming Cable
No Image	MMC-00006-A	DC Jack Connector	MM - Mechanical Module	CUI Devices, Kycon, SparkFun, Adafruit	The 9V DC Jack Connector is a power connector used to supply DC power to electronic circuits and devices. It provides a secure connection between power adapters and systems. It is commonly used in Arduino projects, robotics, embedded systems, and DIY electronics for stable power delivery.	Connector Type: DC Barrel Jack Input Voltage: 9V DC Connector Size: 5.5mm x 2.1mm	DC jack • 9V connector • barrel jack • power connector • DC socket • Arduino power jack

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	MMD-00002-A	Metal Gear Servo	MM - Mechanical Module	TowerPro, DFRobot, Adafruit, SparkFun, Robocraze	The MG995 360° High Torque Servo Motor is a continuous rotation servo used in robotics, RC vehicles, robotic arms, automation systems, smart wheel drives, and Arduino projects. It features metal gears, PWM control, and high torque for strong and reliable performance. Its continuous rotation makes it ideal for motion control and automation applications.	Product Type: Digital Servo Motor Model: MG995 Rotation Type: 360° Continuous Rotation Operating Voltage: 4.8V – 7.2V DC Stall Torque: 9kg-cm – 13kg-cm	Arduino Servo • Digital Servo Motor • Metal Gear Servo • High Torque Servo • Robotics Servo • MG995 Servo • 360° Servo Motor
	MMD-00002-B	Servo Motor	MM - Mechanical Module	TowerPro, MWduino Compatible, Generic	Compact 9g micro servo motor with 180° rotation for precise position control. Provides 1.2–1.6 kg-cm torque and fast response, making it ideal for robotics, RC models, automation, and educational projects. Compatible with Arduino and other microcontrollers using standard PWM signals. Lightweight, reliable, and easy to integrate into DIY and prototyping applications.	Item Type: TowerPro Servo Motor Model Series: SG Series Model No.: SG90 Rotation (Degree): 180° Torque Rating (kg-cm): 1.2 to 1.6 Operating Voltage (VDC): 3.0 – 7.2 Operating Speed @ 4.8V: 0.10 sec/60° Stall Torque @ 4.8V (kg-cm): 1.2 Stall Torque @ 6.6V (kg-cm): 1.6 Operating Temperature (°C): -30 to 60 Gear Type: Glass Fiber Servo Plug Type: JR Cable Length (cm): 25 Length (mm): 22.8 Width (mm): 12.6 Height (mm): 34.5 Weight (g): 9 Shipping Weight: 0.014 kg Shipping Dimensions (L × W × H): 8 × 6 × 4 cm	SG90 Servo • 9g Servo Motor • Micro Servo • RC Servo • Arduino Servo
	MMD-00002-D	Digital Servo Motor	MM - Mechanical Module	TowerPro, Probots, DFRobot, Adafruit, SparkFun	The MG996R 360° Digital Servo Motor is a high-torque continuous rotation servo used in robotics, robotic arms, RC vehicles, automation systems, pan-tilt platforms, and Arduino projects. It features strong metal gears and PWM control for smooth and reliable operation. Its full 360° continuous rotation makes it ideal for applications requiring controlled motion and high torque.	Product Type: Digital Servo Motor Model: MG996R Rotation Type: 360° Continuous Rotation Operating Voltage: 4.8V – 7.2V DC Rated Voltage: 6V DC Stall Torque: 10kg-cm – 13kg-cm	Arduino Servo • MG996R Servo • 360 Degree Servo • Digital Servo Motor • Metal Gear Servo • High Torque Servo • Robotics Servo
	MMD-00003-A	Micro gear motor	MM - Mechanical Module	Pololu, DFRobot, Adafruit, SparkFun	N20 micro gear motors are compact DC motors with integrated metal gearboxes that provide low-speed, high-torque performance in a small size. They are widely used in robotics, smart cars, line follower robots, automation systems, and DIY electronics projects. Their compact design makes them ideal for space-constrained and educational applications requiring precise and reliable motion control.	Product Type: Micro Gear Motor Operating Voltage: 3V – 12V DC Rated Voltage: 6V DC Speed Range: 15RPM – 1000RPM Shaft Diameter: 3 mm	Mini Motor • Arduino Motor • Robotics Motor • Metal Gear Motor • N20 Motor • Micro Gear Motor • DC Gear Motor
	MMD-00003-B	150 RPM Geared Motor	MM - Mechanical Module	Johnson Motor, DFRobot, Robu.in, FlyRobo	The 150 RPM 12V geared DC motor is a high-torque motor with an integrated gearbox for efficient and controlled motion. It reduces speed while increasing torque, making it suitable for robotics, smart vehicles, automation systems, conveyor mechanisms, and DIY projects. It is ideal for Arduino-based applications requiring precise and reliable movement.	Product Type: DC Geared Motor Rated Voltage: 12V DC Speed: 150 RPM Gearbox Type: Metal Gearbox Shaft Diameter: 6 mm Current Consumption: 100mA – 500mA	150RPM Motor • Geared DC Motor • 12V Gear Motor • High Torque Motor • Robotics Motor • DIY Motor • Metal Gear Motor
	MMD-00004-A	Vibrating Motor	MM - Mechanical Module	Precision Microdrives, Adafruit, Jinlong Machinery, Generic Motors, DFRobot	DC vibrating motors are compact motors with an off-center weight that creates vibration when the motor rotates. They are widely used in mobile phones, wearables, robotics, alert systems, haptic feedback devices, and Arduino projects. Lightweight and easy to use, they are ideal for DIY electronics and interactive applications.	Product Type: Vibrating DC Motor Operating Voltage: 1.5V – 5V DC Speed: 8000 – 12000 RPM Current Consumption: 60mA – 100mA	Mini Motor • Arduino Motor • Vibration Motor • Vibrating Motor • Coin Motor • DC Vibration Motor • Haptic Motor
	MMD-00005-A	Mini Water Pump	MM - Mechanical Module	Adafruit, SunFounder, DFRobot, Generic Pump Manufacturer	Mini submersible water pumps are compact DC-powered pumps used for water circulation in fountains, aquariums, hydroponics, cooling systems, and automatic watering projects. They operate fully submerged and provide smooth, low-noise, continuous water flow. Lightweight and easy to install, they are ideal for Arduino, DIY, and educational applications.	Product Type: Mini Submersible Water Pump Operating Voltage: 3V – 6V DC Rated Voltage: 5V DC Current Consumption: 100mA – 220mA Flow Rate: 80 – 120 L/H Outlet Diameter: 7mm – 8mm	Mini Water Pump • Submersible Pump • DC Water Pump • Aquarium Pump • DIY Pump • Arduino Water Pump • Micro Pump

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	MMM-00001-A	BO Motor	MM - Mechanical Module	FlyRobo, RoboticsDNA, RoboElements	The 100 RPM Dual Shaft BO Motor is a low-voltage DC geared motor used for robotics and motion control. It provides good torque at 3–6V and features a dual shaft for easy wheel mounting. It is widely used in robot cars, DIY projects, and educational kits.	Gearbox Shape: Straight Operating Voltage: 3 ~ 6 V Rated Speed After Reduction: 100 RPM Shaft Diameter: 0.55 cm (Double) Shaft Length: 0.85 cm Dimensions (LxWxH): 7 x 2.3 x 1.9 cm	robotics • arduino • BO Motor • Gear Motor • Smart Car
	MMM-00005-A	Wheels	MM - Mechanical Module	Pololu, DFRobot, Waveshare, SunFounder	N20 34mm rubber wheels are compact wheels designed for N20 micro gear motors with a 3mm D-shaft. Used in line follower robots, mini smart cars, obstacle avoidance robots, STEM kits, and DIY robotics projects, they offer easy press-fit mounting. The rubber surface provides good grip, stability, and smooth motion on different surfaces.	Product Type: N20 Motor Rubber Wheel Wheel Diameter: 34 mm Wheel Width: 6.5 mm – 7 mm Shaft Type: 3 mm D Shaft	Rubber Wheel • Smart Car Wheel • DIY Robot Wheel • N20 Wheel • 34mm Robot Wheel • N20 Motor Wheel • Mini Robot Wheel
No Image	MMM-00005-B	Rubber wheels	MM - Mechanical Module	DFRobot, Pololu, SparkFun, Waveshare	Rubber wheels for DC motors are used in robotics, Arduino car kits, line follower robots, obstacle avoidance robots, and DIY projects. They fit BO and TT geared motors and provide good grip, stability, and smooth movement on different surfaces. Made from durable rubber, they are ideal for educational and prototyping applications.	Product Type: Rubber Wheel for DC Motor Wheel Diameter: 65mm / 70mm Compatible Motors: BO Motor / TT Motor Wheel Width: 25mm – 30mm	Robot Wheel • Rubber Wheel • DC Motor Wheel • Smart Car Wheel • Tyre Wheel • DIY Robot Wheel • Motor Wheel
	MMM-00006-A	Castor wheel	MM - Mechanical Module	Blickle, TENTE, Shepherd Hardware, Caster Concepts	1-inch castor wheels are small wheels used for robotics, DIY platforms, trolleys, furniture, and movable enclosures. Available in swivel and fixed types, they provide smooth and easy movement. Made from plastic, rubber, or nylon, they are durable and suitable for lightweight mobility and prototyping applications.	Product Type: Castor Wheel Wheel Size: 1 inch Load Capacity: 5kg – 20kg Rotation: 360° Swivel	DIY Hardware • Castor Wheel • 1 Inch Wheel • Mini Castor • Swivel Wheel • Furniture Wheel • Robot Wheel
	MMP-00001-A	Spacers	MM - Mechanical Module	Keystone Electronics, Adafruit, DFRobot, Pro'sKit	Spacers are mechanical components used to maintain precise distance between PCBs, panels, enclosures, and mounted parts in electronics, robotics, Arduino, and DIY projects. They provide support, alignment, and insulation, preventing unwanted contact between components. Available in nylon, brass, aluminum, and stainless steel variants for different applications.	Product Type: Spacer / Standoff Thread Size: M3 Length Options: 5mm – 50mm	PCB Spacer • Mounting Spacer • DIY Hardware • Spacer • Nylon Spacer • Brass Spacer • Standoff Spacer
	MMP-00002-A	Fastening Nuts	MM - Mechanical Module	Unbrako, TVS Fasteners, Bossard, RS PRO	Nuts are threaded fasteners used with bolts and screws to securely join components in mechanical and electronic assemblies. They are widely used in robotics, PCB mounting, enclosures, 3D printing, machinery, and DIY projects. Available in types like hex nuts, lock nuts, nylon insert nuts, and flange nuts, they provide strong and reliable fastening support.	Product Type: Hex Nut Nut Size: M3 Compatible With: M3 Screws & Bolts	DIY Hardware • Hex Nut • M3 Nut • Lock Nut • Machine Nut • Fastener Nut • Mounting Hardware
	TLC-00001-A	Cutting mat	TL - Tools	OLFA, Deli, Fiskars, Pro'sKit	An A2 cutting mat is a self-healing protective work surface used for cutting paper, vinyl, fabric, PCB sheets, foam, leather, and craft materials. It protects tables and blades while providing printed measurement grids for accurate cutting in DIY, electronics, art, and workshop applications.	Product Type: Self Healing Cutting Mat Size: A2 Dimensions: Approx. 600 × 450 mm Material: PVC Multi-layer Thickness: 2 mm – 3 mm	Cutting Mat • A2 Cutting Mat • Self Healing Mat • Craft Mat • DIY Cutting Board • Precision Cutting Mat • Workshop Mat

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	TLC-00007-A	Desolder Pump	TL - Tools	Generic / OEM, Noel, Pro'sKit, Velleman, Engineer	A desoldering pump is a handy tool used to remove molten solder from PCBs during repairs and component replacement. It uses a spring-loaded plunger and heat-resistant nozzle to create strong suction, quickly clearing solder from joints. Lightweight, portable, and easy to use, it helps ensure clean desoldering while reducing the risk of damage to delicate electronic components.	Item Type: Desoldering Pump Body Material: Aluminum or Plastic Tip Material: Heat-resistant Teflon Color: Blue / Silver Length: 190 mm Width: 30 mm Height: 30 mm Weight: 29 g Shipping Weight: 0.03 kg Shipping Dimensions: 17 × 12 × 3 cm	PCB Rework • Desoldering Pump • Solder Sucker • Manual Vacuum • Teflon Tip
	TLM-00002-A	Wire Cutter	TL - Tools	Generic / OEM, Pro'sKit, Knipex	A diagonal wire cutter is a precision hand tool designed for clean and accurate cutting of electrical wires, component leads, and soft metals. It features ergonomic non-slip grip handles for comfort and a spring-loaded mechanism that reduces hand fatigue during extended use. Compact, durable, and easy to handle, it is ideal for electronics assembly, repairs, prototyping, and DIY projects.	Item Type: Diagonal Wire Cutter Material: High-Carbon Steel Blade with ABS Handle Color: Blue Length (mm): 185 Width (mm): 95 Height (mm): 15 Weight: 60 g Shipping Weight: 0.062 kg Shipping Dimensions: 19 × 10 × 2 cm	Diagonal Cutter • Wire Cutter • Cutting Pliers • Side Cutter • Electrical Tool
	TLM-00004-A	Metal Hacksaw Blade	TL - Tools	Taparia Tools Ltd, Stanley Tools, Bosch, DeWalt, JK Files & Tools, Ultra Tools	Metal cutting hacksaw blades are used for cutting steel, iron, aluminum, copper, pipes, rods, and metal sheets. Made from bi-metal or HSS, they offer good strength, sharpness, and durability. Higher TPI gives smoother and more precise cuts. These blades are widely used in workshops, fabrication, maintenance, and DIY metalworking projects for reliable cutting performance.	Blade Length: 150 mm / 300 mm Material: Bi-Metal / HSS / Carbon Steel Application: Metal Cutting, Workshop, DIY	Hacksaw Blade • Metal Cutting Blade • Bi-Metal Blade • DIY Tool Blade • HSS Blade • Steel Cutting Blade • Hand Saw Blade
	TLM-00004-B	Wood Saw Blade	TL - Tools	Taparia Tools Ltd, Stanley Tools, Ingco Tools, DeWalt	Wood cutting hacksaw blades are designed for cutting soft wood, plywood, PVC, and plastic materials. With a lower TPI design, they allow faster cutting and efficient material removal. These blades provide smooth performance and good durability, making them suitable for woodworking, craft projects, repairs, and DIY applications where quick and reliable cutting is required.	Blade Length: 150 mm / 300 mm Material: Carbon Steel / Bi-Metal Suitable Material: Wood, PVC, Plastic Application: DIY, Carpentry, School Projects	Hacksaw Blade • Carbon Steel Blade • Wood Cutting Blade • Mini Hacksaw Blade • Junior Blade • DIY Tool Blade
	TLM-00004-C	Mini hacksaw	TL - Tools	Stanley, Taparia, Lenox	A mini hacksaw is a compact hand tool used for cutting metal rods, PVC pipes, plastic sheets, bolts, and small materials with precision. Its lightweight and ergonomic design makes it easy to use in tight spaces. Commonly used in electronics labs, robotics projects, plumbing, maintenance work, and DIY applications, it provides reliable and controlled cutting performance for everyday tasks.	Blade Length: 150 mm / 6 inch / 10 inch Handle Type: Ergonomic Grip / ABS Handle Weight: Approx. 70g – 250g Usage: DIY, Electronics, Plumbing, Workshop Cutting Material: Metal, PVC, Plastic, Aluminum	DIY Tool • Mini Hacksaw • Junior Hacksaw • Hand Saw • Metal Cutter • Compact Saw • Precision Cutting Tool
	TLM-00005-A	Micro longnose Plier	TL - Tools	Proskit, Taparia, Jakemy, tanley	Micro long nose pliers are compact precision hand tools designed for electronics repair, PCB assembly, wire bending, and handling small components. Their slim, pointed jaws allow easy access to tight and confined spaces, making them ideal for detailed work. Commonly used in robotics, DIY electronics, jewelry making, and maintenance tasks, they provide accurate control and reliable performance.	Size: 4.5 inch – 5 inch Handle Type: Soft Grip / Anti-slip Usage: Precision Gripping & Wire Bending	DIY Tool • Needle Nose Plier • Mini Plier • Micro Long Nose Plier • Precision Plier • Electronics Tool • Jewelry Plier

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	TLP-00001-A	Hot Melt Glue Gun	TL - Tools	Generic / OEM, Stanley, Bosch, Pro'sKit	A 40W hot melt glue gun is a versatile tool designed for bonding, crafting, repairs, and DIY projects. It features a standard operating temperature, ergonomic trigger mechanism for precise glue flow control, and an integrated ON/OFF switch for added safety and convenience. Compatible with standard glue sticks, it delivers strong adhesion and reliable performance for various materials.	Item Type: Hot Melt Glue Gun Color: Black Operating Voltage: 110–220 V AC Power Consumption: 40 W Melting Point: 190°C (±10°C) Compatible Glue Stick Diameter: 7 mm Weight: 180 g Shipping Weight: 0.2 kg Shipping Dimensions: 27 × 16 × 5 cm	Compatible with 11mm diameter glue sticks and suitable for DIY projects • electronics work • furniture repair • decoration • packaging • and household fixes.
	TLP-00003-A	Soldering Iron Stand	TL - Tools	Generic / OEM, Pro'sKit, Velleman, Goot, Noel	The 25W Soldering Iron Stand is used to safely hold soldering irons during work. It has a stable metal base and a spring holder for secure placement. It is commonly used in electronics labs, DIY projects, and repair workstations.	Suitable Wattage: 25 Watt (Max) Material: Metal Base with Steel Spring Holder Shipping Weight: 0.3 kg Shipping Dimensions: 20 × 6 × 3 cm	Soldering Stand • 25W • Iron Holder • Metal Base • Spring Holder