





Parts Export

Generated: 2026-04-19 14:22:04

Total Parts: 4

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EDM-00001-A	Tactile Push Button Switch Round Key (12x12x7.3mm, 25PCS Kit)	ED - Electronic Device	OMRON, E-Switch	12x12x7.3mm tactile push button switches with momentary ON-OFF operation. Rated for 12V DC and 120mA with responsive tactile feedback. Includes 25 color-coded round keycaps and storage box for prototyping and DIY projects.	Item Type: Micro Switch Model: Tactile Push Button Switch Operation Mode: ON-OFF Contact Type: Momentary Current Rating: 120mA Operating Voltage: 12V DC Switch Type: Push Button Material: Metal and Plastic Mounting Type: Surface Mount Button Size (mm): 12x12x7.3 Operating Temperature (°C): -25 to +70 Lifespan: ~1000 Cycles Box Dimensions (mm): 127.1 x 68.3 x 21.9 Weight (g): 55 Shipping Weight: 0.06 kg Shipping Dimensions (L x W x H): 13 x 7 x 3 cm	Tactile Switch • Push Button • 12x12mm Switch • Momentary Switch • Arduino Button Kit
	EMA-00003-B	WS2812B 8-Bit RGB NeoPixel LED Module (8x 5050 LEDs)	EM - Electronic-Electrical Modules	Worldsemi Co., Ltd., Generic / OEM	The WS2812B 8-Bit RGB LED Module features 8 individually addressable 5050 RGB LEDs with integrated driver ICs. It operates on 5V and uses a single-wire communication protocol for precise color and brightness control. Ideal for programmable lighting, animations, IoT devices, and Arduino-based creative projects.	LED Model: WS2812B Package Type: 5050 SMD Number of LEDs: 8 Color Type: Full-Color RGB Bit Depth: 8-bit per channel (24-bit RGB total) Operating Voltage: DC 5V Control Interface: Single Data Line (Serial) Communication Protocol: One-Wire Timing Protocol PCB Color: White Mounting Type: Solderless / Plug-and-Play Length (mm): 105 Width (mm): 10 Height (mm): 6 Weight (g): 8 Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H cm): 12 x 8 x 1	Arduino Compatible • WS2812B • NeoPixel Module • 8 LED RGB • 5050 SMD • Addressable LED • 5V RGB Strip • Programmable LED
	EMA-00008-A	Single Channel Relay Module (12V, High/Low Level Trigger)	EM - Electronic-Electrical Modules	Single Relay, Generic / OEM	The Single Channel 12V Relay Module allows low-voltage microcontrollers to safely control high-voltage AC or DC loads. It supports both high-level and low-level trigger modes and includes status LEDs for operation indication. Ideal for home automation, motor control, IoT systems, and industrial switching applications.	Model: Relay Module Number of Channels: 1 Operating Voltage (VDC): 12 Trigger Type: High-Level / Low-Level Trigger Relay Contact Rating (AC): 10A @ 250V AC Relay Contact Rating (AC Alternate): 15A @ 125V AC Contact Type: COM, NO (Normally Open), NC (Normally Closed) Interface: 2.54 mm Header Pins Output Connection: 3-Pin Screw Terminal Indicators: Power LED + Relay Status LED Length (mm): 50 Width (mm): 25 Height (mm): 20 Weight (g): 16 Shipping Weight: 0.025 kg Shipping Dimensions (L x W x H cm): 7 x 4 x 3	Arduino Compatible • 12V Relay Module • Single Channel Relay • High/Low Trigger • Single SRD-12VDC-SL-C • SPDT Relay • 10A 250VAC • IoT Switching Module
	EMP-00001-C	12V 2A SMPS Power Adapter	EM - Electronic-Electrical Modules	Generic / OEM, Mean Well, Delta Electronics, LEICKE	12V 2A Switched Mode Power Supply (SMPS) adapter designed to provide stable and regulated DC output. Converts AC 100-240V input to 12V DC output with low losses and high efficiency compared to conventional linear power supplies. Suitable for powering Arduino boards, routers, LCD displays, DC motors, audio equipment, TV boxes, mini electronics, and other devices requiring up to 2A current.	Input Voltage: 100-240V AC Output Voltage: 12V DC Maximum Output Current: 2A Output Connector Size: 5.5 x 2.5 mm Polarity: Center Positive Operating Temperature: -25°C to +60°C Shipping Weight: 0.02 kg Shipping Dimensions: 10 x 6 x 6 cm	12V Adapter • 12V 2A Power Supply • SMPS Adapter • AC-DC Adapter • 5.5x2.5mm Power Adapter