

# Parts Export

Generated: 2026-04-19 14:22:04

Total Parts: 12













Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COE-00001-C	CR2025 3V Lithium Coin Cell	CO - Consumables	Panasonic	.Panasonic CR2025 is a 3V lithium coin cell battery designed for long-lasting and reliable power in compact electronic devices.&nbsp;&nbsp;&nbsp;Built using Lithium Manganese Dioxide (LiMnO?) chemistry, it offers stable discharge characteristics and a shelf life of up to 10 years under proper storage conditions.&nbsp;&nbsp;&nbsp;Suitable for car key remotes, medical devices, digital watches, calculators, fitness devices, memory backup systems, and other small electronics.	Battery Type: Lithium Coin Cell Battery Size: CR2025 Chemistry: Lithium Manganese Dioxide (LiMnO?) Nominal Voltage: 3 V Nominal Capacity: 165 mAh Diameter: 20 mm Height: 2.5 mm Termination Style: Pressure Contacts Operating Temperature: -30°C to +60°C Weight (Unit): 2.3 g Shipping Weight: 0.008 kg Shipping Dimensions: 9.2 x 7.5 x 1 cm	CR2025 Battery • 3V Coin Cell • Lithium Battery • Panasonic Battery • Button Cell
	EDM-00001-A	Tactile Push Button Switch Round Key (12x12x7.3mm, 25PCS Kit)	ED - Electronic Device	OMRON, E-Switch	12x12x7.3mm tactile push button switches with momentary ON-OFF operation.Rated for 12V DC and 120mA with responsive tactile feedback.Includes 25 color-coded round keycaps and storage box for prototyping and DIY projects.	Item Type: Micro Switch Model: Tactile Push Button Switch Operation Mode: ON-OFF Contact Type: Momentary Current Rating: 120mA Operating Voltage: 12V DC Switch Type: Push Button Material: Metal and Plastic Mounting Type: Surface Mount Button Size (mm): 12x12x7.3 Operating Temperature (°C): -25 to +70 Lifespan: ~1000 Cycles Box Dimensions (mm): 127.1 x 68.3 x 21.9 Weight (g): 55 Shipping Weight: 0.06 kg Shipping Dimensions (L x W x H): 13 x 7 x 3 cm	Tactile Switch • Push Button • 12x12mm Switch • Momentary Switch • Arduino Button Kit
	EDR-00001-100Z	0.25W Resistor - 100 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	1. 100 ohm Carbon Film Resistors are typical axial-lead resistors, which have much better temperature stability and provide lower noise, and are generally better for high frequency or radiofrequency applications. 2. We made it available in the form of a bunch of different values as required for the project to provide convenience, so you need not find a differently required value resistor at different places while working on your project.	Series: – Resistance (Ohm): 100 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	resistor • 100ohm • carbon film • passive component
	EDR-00001-10K0	0.25W Resistor - 10K Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	1.10K/100? Carbon Film Resistors are typical axial-lead resistors that offer good temperature stability and low noise performance. They are suitable for general-purpose electronic circuits, including high-frequency and RF applications. 2.These resistors are available in multiple values for project flexibility, eliminating the need to source different resistor values separately.	Power: 1/4 W Resistance: 100 ? Resistance Tolerance: 5% Type: Carbon Film Resistors	Through Hole • carbon film • 10k resistor • 0.25w • passive • axial
	EDR-00001-1K00	0.25W Resistor - 1K Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	1K ohm Carbon Film Resistors are typical axial-lead resistors, which have much better temperature stability and provide lower noise, and are generally better for high frequency or radiofrequency applications.	Series: – Resistance (Ohm): 1k Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	carbon film • 0.25w • passive • 1k resistor
	EDR-00001-1M00	0.25W Resistor - 1M Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 1M Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: - Resistance (Ohm): 1M Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	0.25w • passive • 1m resistor • metal film
	EDR-00001-220Z	0.25W Resistor - 220 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 220 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 220 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EDR-00001-330Z	0.25W Resistor - 330 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 330 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 330 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	
	EDR-00001-470Z	0.25W Resistor - 470 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 470 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Power: 1/4 W Resistance: 47k ? Resistance Tolerance: 5% Type: Carbon Film Resistors	resistor • carbon film • 0.25w • passive • axial • 470ohm
	EDR-00001-680Z	0.25W Resistor - 680 Ohm	CO - Consumables	Yageo, Vishay, KOA Speer, TE Connectivity, Generic	It is a 680 Ohm 0.25W Metal Film Resistor. This resistor is for through-hole applications.	Series: – Resistance (Ohm): 680 Tolerance (%): 1 Power Rating: 250mW Composition: Metal Film Temperature Coefficient: +/- 50ppm/°C Operating Temperature (°C): -40 ~ 150 Case/Package: Axial Length (mm): 6 Mounting Type: Through Hole Shipping Weight: 0.001 kg Shipping Dimensions: 1 x 1 x 1 cm	resistor • carbon film • 0.25w • passive • axial • 680ohm
	TLP-00002-A	Soldering Iron Kit – 3-in-1 (25W)	TL - Tools	TLP Series / Generic Compatible, Noel, Pro'sKit, Velleman	Be it beginner, hobbyist, or professional, soldering iron kits are essential tools for building circuit boards, repairing electronics, jewelry making, welding, and other precision tasks. This kit combines the basic tools used in general-purpose soldering work and includes necessary components required for soldering at your work desk. Best suited for DIY beginners, college project teams, and professional electronics hobbyists.	Item Type: Kit Soldering Iron Power: 25 Watt Suitable For: Beginner to Professional Shipping Weight: 0.4 kg Shipping Dimensions: 20 x 7 x 6 cm	Soldering Kit • 25W Soldering Iron • 3-in-1 Kit • DIY Soldering Set • Electronics Repair Kit
	TLP-00003-A	Soldering Iron Stand (25W Compatible)	TL - Tools	Generic / OEM, Pro'sKit, Velleman, Goot, Noel	The soldering iron stand 25W is a standardized support tool designed for safely holding soldering irons during operation. It is compatible with 25W or lower wattage soldering irons. The stand features a heavy-duty metal base for stability and a nickel-plated spring holder that securely holds the soldering iron while not in use. Ideal for electronics workbenches, college labs, DIY projects, and professional repair environments.	Suitable Wattage: 25 Watt (Max) Material: Metal Base with Steel Spring Holder Shipping Weight: 0.3 kg Shipping Dimensions: 20 x 6 x 3 cm	Soldering Stand • 25W • Iron Holder • Metal Base • Spring Holder