


# Parts Export

Generated: 2026-04-19 12:53:03

Total Parts: 1

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	<b>EDD-00003-A</b>	RGB Multi-Color LED Module (Common Cathode, 5mm)	ED - Electronic Device	ED Series / XINGLIGHT, XINGLIGHT	5mm common cathode RGB LED with transparent lens for multi-color indication. Combines red and green-yellow emission in a single through-hole package. Ideal for indicator panels, DIY electronics, and visual feedback systems.	Manufacturer: XINGLIGHT Model No.: XL-A524SURSYGC Package: Plugin, D = 5mm Forward Current (mA): 20 Color Temperature: - Peak Wavelength (nm): 640 (Red) 572 (Green: Yellow) Luminous Intensity (mcd): 600 (Red) 550 (Green: Yellow) Lens Color: Colorless Transparent Diode Configuration: Common Cathode Wavelength – Dominant (nm): 635–640 (Red) 565–575 (Green: Yellow) Operating Temperature (°C): -20 ~ +85 Illumination Color: Red, Green-Yellow Viewing Angle: 30° Lamp Holder Type: 5mm Round Head Power (mW): 50 Forward Voltage (Vf): 2.3V (Red) 2.4V (Green: Yellow) Mounting Type: Through Hole Compliance: RoHS	RGB LED • 5mm LED • Common Cathode LED • Indicator LED • Through Hole LED